



CA3106F32-5PXF80 Information

Heisener.com

Part Number CA3106F32-5PXF80 **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 2POS INLINE W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3106F32-5PXF80 Specifications

Manufacturer Part Number Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 2 Shell Size - Insert 32-5 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation X Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated Supratur Bating 245 A		
Category Circular Connectors Circular Connectors Package - Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 2 Shell Size - Insert 32-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation X Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Source Circular Connectors MIL-DTL-5015, CA MIL-DTL-5015, CA MIL-DTL-5015, CA MIL-DTL-5015, CA MIL-DTL-5015, CA MIL-DTL-5015, CA MIL-DTL-5015, CA Plug, Male Pins 2 Connector Type Free Hanging (In-Line) Tremination Crimp Fastening Type Threaded Orientation X Ingress Protection Silver Features - Voltage - Rated	Manufacturer Part Number	CA3106F32-5PXF80
Circular Connectors Package Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 2 Shell Size - Insert 32-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation X Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Contact Fasted Contact Fa	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 2 Shell Size - Insert 32-5 Shell Size, MIL - Crimp Termination Crimp Fastening Type Threaded Orientation X Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated MIL-DTL-5015, CA MIL-DTL-5	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 2 Shell Size - Insert 32-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation X Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationXIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50V	Package	-
Number of Positions Shell Size - Insert 32-5 Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation X Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 22 32-5 Free Hanging (In-Line) Crimp Threaded Crimp Threaded Aluminum Alloy, Olive Drab Cadmium Plated Silver Features - Voltage - Rated	Series	MIL-DTL-5015, CA
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation X Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 32-5 Siver Free Hanging (In-Line) Trimp Aluminum Alloy Silver Features - Voltage - Rated	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation X Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 50V	Number of Positions	2
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationXIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50V	Shell Size - Insert	32-5
Termination Crimp Fastening Type Threaded Orientation X Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V	Shell Size, MIL	-
Fastening Type Threaded Orientation X Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V	Mounting Type	Free Hanging (In-Line)
Orientation X Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V	Termination	Crimp
Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Aluminum Alloy, Olive Drab Cadmium Plated Silver - 50V	Orientation	X
Contact Finish Silver Features - Voltage - Rated 50V	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features - Voltage - Rated 50V	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V	Contact Finish	Silver
-	Features	-
Current Poting 245A	Voltage - Rated	50V
Current Rating 243A	Current Rating	245A
Report errors?		Report errors?

CA3106F32-5PXF80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3106F32-5PXF80 Payment Methods



















CA3106F32-5PXF80 Shipping Methods













If you have any question about CA3106F32-5PXF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com