



CA3106F32-7PB15 Information

Heisener.com

Part Number CA3106F32-7PB15 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 35POS INLINE W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3106F32-7PB15 Specifications

Manufacturer Part Number CA3106F32-7PB15 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Male Pins Number of Positions 35 Shell Size - Insert 32-7 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 22A, 41A Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Male PinsNumber of Positions35Shell Size - Insert32-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated50VCurrent Rating22A, 41A	Manufacturer Part Number	CA3106F32-7PB15
Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Male Pins Number of Positions 35 Shell Size - Insert 32-7 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated Current Rating 22A, 41A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-B Connector Type Plug, Male Pins Number of Positions 35 Shell Size - Insert 32-7 Shell Size, MIL - Crimp Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 222A, 41A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-B Connector Type Plug, Male Pins Number of Positions 35 Shell Size - Insert 32-7 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 22A, 41A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions35Shell Size - Insert32-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated50VCurrent Rating22A, 41A	Package	-
Number of Positions35Shell Size - Insert32-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated50VCurrent Rating22A, 41A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 22A, 41A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Rastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated 50V Current Rating 22A, 41A	Number of Positions	35
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated50VCurrent Rating22A, 41A	Shell Size - Insert	32-7
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 22A, 41A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 22A, 41A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 22A, 41A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 22A, 41A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Shielded Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Shielded 22A, 41A	Orientation	N (Normal)
Contact Finish Silver Shielded Voltage - Rated Current Rating 22A, 41A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Shielded Voltage - Rated 50V Current Rating 22A, 41A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A, 41A	Contact Finish	Silver
Current Rating 22A, 41A	Features	Shielded
-	Voltage - Rated	50V
Report errors?	Current Rating	22A, 41A
		Report errors?

CA3106F32-7PB15 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3106F32-7PB15 Payment Methods



















CA3106F32-7PB15 Shipping Methods













If you have any question about CA3106F32-7PB15, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com