



## CA3106R24-28SF80 Information

Heisener.com

**Part Number** CA3106R24-28SF80 **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

**Description** CONN PLUG 24POS INLINE W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## CA3106R24-28SF80 Specifications

Manufacturer Part NumberCA3106R24-28SF80ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypePlug, Female SocketsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50V		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypePlug, Female SocketsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50V	Manufacturer Part Number	CA3106R24-28SF80
Circular Connectors  Package Series MIL-DTL-5015, CA Connector Type Plug, Female Sockets Number of Positions 24 Shell Size - Insert 24-28 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated  Circular Connectors  MIL-DTL-5015, CA MIL-DTL-5015, CA Plug, Female Sockets NIL-DTL-5015, CA Plug, Female Sockets NIL-DTL-5015, CA Plug, Female Sockets NIL-DTL-5015, CA Plug, Female Sockets Number of Positions 14-29 Prese Hanging (In-Line) Prese	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA Connector Type Plug, Female Sockets Number of Positions 24 Shell Size - Insert 24-28 Shell Size, MIL - Characteria 24-28 Shell Size, MIL - Crimp Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CAConnector TypePlug, Female SocketsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50V		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50V	Package	-
Number of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50V	Series	MIL-DTL-5015, CA
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Voltage - Rated  24-28  Auminum Alloy  Ingress Protection  Silver  -  Voltage - Rated  50V	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Features - Voltage - Rated 50V	Number of Positions	24
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50V	Shell Size - Insert	24-28
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V	Shell Size, MIL	-
Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  IP65 - Dust Tight, Water Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Voltage - Rated  Threaded  N (Normal)  IP65 - Dust Tight, Water Resistant  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Foatures  - Voltage - Rated	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V	Termination	Crimp
Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50V	Fastening Type	Threaded
Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 50V	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated 50V	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features - Voltage - Rated 50V	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V	Contact Finish	Silver
	Features	-
	Voltage - Rated	50V
Current Rating 22A	Current Rating	22A
Report errors?		Report errors?

#### CA3106R24-28SF80 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

#### CA3106R24-28SF80 Payment Methods



















### CA3106R24-28SF80 Shipping Methods













If you have any question about CA3106R24-28SF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com