



## CA3106R32-1SBF80 Information

Heisener.com

Part Number CA3106R32-1SBF80 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects **Circular Connectors** 

**Description** CONN PLUG 5POS INLINE W/SKTS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CA3106R32-1SBF80 Specifications

Manufacturer Part Number       CA3106R32-1SBF80         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-5015, CA-B         Connector Type       Plug, Female Sockets         Number of Positions       5         Shell Size - Insert       32-1         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Fastening Type       Reverse Bayonet Lock         Orientation       N (Normal)         Ingress Protection       IP67 - Dust Tight, Waterproof         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       -         Voltage - Rated       50V         Current Rating       41A, 245A		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 5 Shell Size - Insert 32-1 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Current Rating 41A, 245A	Manufacturer Part Number	CA3106R32-1SBF80
Circular Connectors  Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 5 Shell Size - Insert 32-1 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 50V Current Rating 41A, 245A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 5 Shell Size - Insert 32-1 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 41A, 245A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 5 Shell Size - Insert 32-1 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 245A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert32-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A, 245A	Package	-
Number of Positions5Shell Size - Insert32-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A, 245A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Voltage - Rated  50V  Current Rating  41A, 245A	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Reverse Bayonet Lock Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver  Features - Voltage - Rated 50V  Current Rating 41A, 245A	Number of Positions	5
Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Reverse Bayonet Lock  Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 50V  Current Rating 41A, 245A	Shell Size - Insert	32-1
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 245A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 245A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 245A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 245A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  - 41A, 245A	Orientation	N (Normal)
Contact Finish Silver  Features - Voltage - Rated Current Rating 41A, 245A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 50V Current Rating 41A, 245A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 41A, 245A	Contact Finish	Silver
Current Rating 41A, 245A	Features	-
-	Voltage - Rated	50V
Report errors?	Current Rating	41A, 245A
		Report errors?

#### CA3106R32-1SBF80 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CA3106R32-1SBF80 Payment Methods



















#### CA3106R32-1SBF80 Shipping Methods













If you have any question about CA3106R32-1SBF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com