

Heisener.com

# CA3108E14S-2SF137F187

## CA3108E14S-2SF137F187 Information

Part Number CA3108E14S-2SF137F187

Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 4POS RT ANG W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## CA3108E14S-2SF137F187 Specifications

| Manufacturer Part Number     CA3108E14S-2SF137F187       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-5015, CA       Connector Type     Plug, Female Sockets       Number of Positions     4       Shell Size - Insert     14S-2       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line), Right Angle       Termination     Solder Cup       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     IP65 - Dust Tight, Water Resistant       Shell Material, Finish     Aluminum Alloy, Olive Drab Cadmium Plated       Contact Finish     Silver       Features     Strain Relief       Voltage - Rated     50V       Current Rating     22A |                          |   |
|---|--------------------------|---|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A  | Manufacturer Part Number | CA3108E14S-2SF137F187                     |
| Package-SeriesMIL-DTL-5015, CAConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A   | Manufacturer             | ITT Cannon, LLC                           |
| Package - MIL-DTL-5015, CA Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 14S-2 Shell Size, MIL - CMOUNTING Pree Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating 22A   | Category                 | Connectors, Interconnects                 |
| SeriesMIL-DTL-5015, CAConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A   |                          | Circular Connectors                       |
| Connector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A   | Package                  | -   |
| Number of Positions4Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A   | Series                   | MIL-DTL-5015, CA                          |
| Shell Size - Insert Shell Size, MIL   | Connector Type           | Plug, Female Sockets                      |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line), Right Angle  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief  Voltage - Rated 50V Current Rating 22A   | Number of Positions      | 4   |
| Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A   | Shell Size - Insert      | 14S-2                                     |
| Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A  | Shell Size, MIL          | -   |
| Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A   | Mounting Type            | Free Hanging (In-Line), Right Angle       |
| Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A   | Termination              | Solder Cup                                |
| Ingress Protection  IP65 - Dust Tight, Water Resistant  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  22A  | Fastening Type           | Threaded                                  |
| Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Strain Relief  22A   | Orientation              | N (Normal)                                |
| Contact Finish Silver  Features Strain Relief Voltage - Rated Current Rating 22A  | Ingress Protection       | IP65 - Dust Tight, Water Resistant        |
| Features Strain Relief  Voltage - Rated 50V  Current Rating 22A   | Shell Material, Finish   | Aluminum Alloy, Olive Drab Cadmium Plated |
| Voltage - Rated 50V<br>Current Rating 22A   | Contact Finish           | Silver                                    |
| Current Rating 22A  | Features                 | Strain Relief                             |
|   | Voltage - Rated          | 50V                                       |
| Report errors?  | Current Rating           | 22A                                       |
|   |                          | Report errors?                            |

#### CA3108E14S-2SF137F187 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CA3108E14S-2SF137F187 Payment Methods



















## CA3108E14S-2SF137F187 Shipping Methods













If you have any question about CA3108E14S-2SF137F187, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com