



## CA3108E14S-2SF178 Information

Heisener.com

Part Number CA3108E14S-2SF178 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 4POS RT ANG W/SKTS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CA3108E14S-2SF178 Specifications

Manufacturer Part Number       CA3108E14S-2SF178         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Circular Connectors         Package       -         Series       MIL-DTL-5015, CA         Connector Type       Plug, Female Sockets         Number of Positions       4         Shell Size - Insert       14S-2         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line), Right Angle         Termination       Solder Cup         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       IP65 - Dust Tight, Water Resistant         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       -         Voltage - Rated       50V         Current Rating       22A		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-5015, CA Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 14S-2 Shell Size, MIL  Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 50V Current Rating 22A	Manufacturer Part Number	CA3108E14S-2SF178
Circular Connectors  Package - Series MIL-DTL-5015, CA Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 14S-2 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 50V Current Rating 22A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 14S-2 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 22A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 14S-2 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Package	-
Number of Positions  Shell Size - Insert  14S-2  Shell Size, MIL  Mounting Type  Free Hanging (In-Line), Right Angle  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  IP65 - Dust Tight, Water Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Voltage - Rated  50V  Current Rating  22A	Series	MIL-DTL-5015, CA
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line), Right Angle  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  IP65 - Dust Tight, Water Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Voltage - Rated  50V  Current Rating  22A	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line), Right Angle  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver Features - Voltage - Rated 50V  Current Rating 22A	Number of Positions	4
Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Shell Size - Insert	14S-2
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Termination	Solder Cup
Ingress Protection  IP65 - Dust Tight, Water Resistant  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  IP65 - Dust Tight, Water Resistant  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  - 22A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  -  22A	Orientation	N (Normal)
Contact Finish Silver  Features - Voltage - Rated Current Rating 22A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features - Voltage - Rated 50V Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	-
-	Voltage - Rated	50V
Report errors?	Current Rating	22A
		Report errors?

#### CA3108E14S-2SF178 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CA3108E14S-2SF178 Payment Methods



















# CA3108E14S-2SF178 Shipping Methods













If you have any question about CA3108E14S-2SF178, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com