

CA3108E18-10S

CA3108E18-10S Information

| Heisener.com | CA3108E18-10S ITT Cannon, LLC Connectors, Interconnects Circular Connectors CONN PLUG 4POS RT ANG W/SKTS - For the pricing/inventory/lead time, please contact | |
|--------------------|--|-----------------|
| For Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CA3108E18-10S Specifications

| Manufacturer Part Number CA3108E18-10S Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Category Circular Connectors Package - Series MIL-DTL-5015, CA Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 18-10 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Normal) Ingress Protection Nicormal Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strian Relief Voltage - Rated 50V | | |
|---|--------------------------|---|
| CategoryConnectors, InterconnectsCategoryCircular ConnectorsPackage-SeriesMIL-DTL-5015, CAConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert18-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionAluminum Alley, Olive PraketstantShell Material, FinishSilverFeaturesSilverFortageStrain ReliefVoltage - RatedStrain ReliefVoltage - RatedStolKatendeStolStoler RatendeStoler CupFeaturesStolStoler RatendeStoler CupFeaturesStoler CupStoler RatendeStoler Cup <t< td=""><td>Manufacturer Part Number</td><td>CA3108E18-10S</td></t<> | Manufacturer Part Number | CA3108E18-10S |
| Circular ConnectorsPackage-SeriesMIL-DTL-5015, CAConnector TypePlug, Fenale SocketsNumber of Positions4Shell Size - Insert18-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishSilverFeaturesStrian ReliefVoltage - Rated50VCurrent Rating41A | Manufacturer | ITT Cannon, LLC |
| Package.SeriesMIL-DTL-5015, CAConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert18-10Shell Size, MIL.Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeInreadedOrientationN(Normal)Ingress ProtectionIG5 - Dust Tight, Water ResistantShell Material, FinishSilverFeaturesSilverVoltage - RatedStovAumine AleineStovStorent RatingStovStorent RatingStovS | Category | Connectors, Interconnects |
| SeriesMIL-DTL-5015, CAConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert18-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionP65 - Dust Tight, Water ResistantShell Material, FinishSilverFoaturesStain ReliefVoltage - Rated50VCurrent Rating41A | | Circular Connectors |
| Connector TypePlug, Female SocketsNumber of Positions4Shumber of Positions18-10Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionHofs - Dust Tight, Water ResistantShell Material, FinishSilverFoaturesSilverVoltage - Rated50VKurnen Rating41A | Package | - |
| Number of Positions4Shell Size - Insert18-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishSilverFeaturesStrian ReliefVoltage - Rated50VCurrent Rating41A | Series | MIL-DTL-5015, CA |
| Shell Size - Insert18-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedFeaturesStrian ReliefVoltage - Rated50VCurrent Rating41A | Connector Type | Plug, Female Sockets |
| Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionP65 - Dust Tight, Water ResistantShell Material, FinishAluninum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStain ReliefVoltage - Rated50VKurrent Rating41A | Number of Positions | 4 |
| Mounting TypeFree Hanging (In-Line), Right AngleForminationSolder CupFastening TypeThreadedForientationN (Normal)Ingress ProtectionP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating41A | Shell Size - Insert | 18-10 |
| TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating41A | Shell Size, MIL | - |
| Fastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating41A | Mounting Type | Free Hanging (In-Line), Right Angle |
| OrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating41A | Termination | Solder Cup |
| Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating41A | Fastening Type | Threaded |
| Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating41A | Orientation | N (Normal) |
| Contact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating41A | Ingress Protection | IP65 - Dust Tight, Water Resistant |
| FeaturesStrain ReliefVoltage - Rated50VCurrent Rating41A | Shell Material, Finish | Aluminum Alloy, Olive Drab Cadmium Plated |
| Voltage - Rated50VCurrent Rating41A | Contact Finish | Silver |
| Current Rating 41A | Features | Strain Relief |
| - | Voltage - Rated | 50V |
| Report errors? | Current Rating | 41A |
| | | Report errors? |

CA3108E18-10S Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3108E18-10S Payment Methods





If you have any question about CA3108E18-10S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com