

Heisener.com

CA3108E18-1PA206A176

CA3108E18-1PA206A176 Information

Part Number CA3108E18-1PA206A176

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 10POS RT ANG W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3108E18-1PA206A176 Specifications

Manufacturer Part Number Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 10 Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 22A Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 10 Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 22A	Manufacturer Part Number	CA3108E18-1PA206A176
Circular Connectors Package - Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 10 Shell Size - Insert 18-1 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Manufacturer	ITT Cannon, LLC
Package - Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 10 Shell Size - Insert 18-1 Shell Size, MIL - Tremination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 202A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 10 Shell Size - Insert 18-1 Shell Size, MIL		Circular Connectors
Connector Type Plug, Male Pins Number of Positions 10 Shell Size - Insert 18-1 Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Package	-
Number of Positions Shell Size - Insert 18-1 Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Series	MIL-DTL-5015, CA
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Features Strain Relief Voltage - Rated 50V Current Rating	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 22A	Number of Positions	10
Mounting Type Free Hanging (In-Line), Right Angle Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Shell Size - Insert	18-1
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Termination	Solder Cup
Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating IP65 - Dust Tight, Water Resistant Aluminum Alloy, Zinc Plated, Black Gold Strain Relief 22A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating Aluminum Alloy, Zinc Plated, Black Gold Strain Relief 22A	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features Strain Relief Voltage - Rated 50V Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Zinc Plated, Black
Voltage - Rated 50V Current Rating 22A	Contact Finish	Gold
Current Rating 22A	Features	Strain Relief
-	Voltage - Rated	50V
Report errors?	Current Rating	22A
		Report errors?

CA3108E18-1PA206A176 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3108E18-1PA206A176 Payment Methods



















CA3108E18-1PA206A176 Shipping Methods













If you have any question about CA3108E18-1PA206A176, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com