

Heisener.com

CA3108E18-8PA206A176

CA3108E18-8PA206A176 Information

Part Number CA3108E18-8PA206A176

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 8POS INLINE W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3108E18-8PA206A176 Specifications

Manufacturer Part Number Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 8 Shell Size - Insert 18-8 Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Features Strain Relief Voltage - Rated Surveyt Paring 23A 41A		
Category Circular Connectors Package Package - Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 8 Shell Size - Insert 18-8 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zine Plated, Black Contact Finish Gold Features Voltage - Rated Connectors, Interconnects Circular Connectors - Circular Connectors NIL-DTL-5015, CA - Connector Type Plug, Male Pins 8 8 Selle Guitane - Connector Type Plug, Male Pins Nelle Aluminum Alloy, Right Angle - Contact Finish Gold Strain Relief Voltage - Rated Sov	Manufacturer Part Number	CA3108E18-8PA206A176
Circular Connectors Package - Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 8 Shell Size - Insert 18-8 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated	Manufacturer	ITT Cannon, LLC
Package - Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 8 Shell Size - Insert 18-8 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 8 Shell Size - Insert 18-8 Shell Size, MIL		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions8Shell Size - Insert18-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishGoldFeaturesStrain ReliefVoltage - Rated50V	Package	-
Number of Positions Shell Size - Insert 18-8 Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated 50V	Series	MIL-DTL-5015, CA
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated 18-8 Free Hanging (In-Line), Right Angle Free Hanging (In-Line), Right Angle Free Hanging (In-Line), Right Angle Solder Cup Threaded Solder Cup Threaded N (Normal) Ingress Protection Strain Relief Strain Relief	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated 50V	Number of Positions	8
Mounting Type Free Hanging (In-Line), Right Angle Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated Free Hanging (In-Line), Right Angle Solder Cup Threaded N (Normal) Ingress Protection Solder Cup Threaded Threaded Solder Cup Threaded Threaded Solder Cup Threaded Thr	Shell Size - Insert	18-8
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated 50V	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated 50V	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated 50V	Termination	Solder Cup
Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Gold Features Strain Relief Voltage - Rated 50V	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated Aluminum Alloy, Zinc Plated, Black Gold Strain Relief	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 50V	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features Strain Relief Voltage - Rated 50V	Shell Material, Finish	Aluminum Alloy, Zinc Plated, Black
Voltage - Rated 50V	Contact Finish	Gold
-	Features	Strain Relief
Current Pating 22A 41A	Voltage - Rated	50V
Current Rating 22A, 41A	Current Rating	22A, 41A
Report errors?		Report errors?

CA3108E18-8PA206A176 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3108E18-8PA206A176 Payment Methods





















CA3108E18-8PA206A176 Shipping Methods













If you have any question about CA3108E18-8PA206A176, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com