



# CA3108E36-6P Information

Heisener.com

Part Number CA3108E36-6P Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 6POS RT ANG W/PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CA3108E36-6P Specifications**

Manufacturer Part Number       CA3108E36-6P         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-5015, CA         Connector Type       Plug, Male Pins         Number of Positions       6         Shell Size - Insert       36-6         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line), Right Angle         Termination       Solder Cup         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       IP65 - Dust Tight, Water Resistant         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       Strain Relief         Voltage - Rated       50V         Current Rating       135A, 245A         Report errors?		
Category Circular Connectors  Package Package Package Plug, Male Pins Number of Positions Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated Voltage - Rated Current Rating  Connectors, Interconnects Circular Connectors  MIL-DTL-5015, CA  AllL-DTL-5015, CA  Features AllL-DTL-5015, CA  AllL-DTL-5015, CA  Features AllL-DTL-Features AllL-DTL-Features AllL-DTL-Features AllL-DTL-Featur	Manufacturer Part Number	CA3108E36-6P
Package-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert36-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating135A, 245A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert36-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating135A, 245A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert36-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating135A, 245A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions6Shell Size - Insert36-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating135A, 245A	Package	-
Number of Positions Shell Size - Insert 36-6 Shell Size, MIL  Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating 135A, 245A	Series	MIL-DTL-5015, CA
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 135A, 245A	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line), Right Angle  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 135A, 245A	Number of Positions	6
Mounting Type Free Hanging (In-Line), Right Angle  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection IP65 - Dust Tight, Water Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 50V  Current Rating 135A, 245A	Shell Size - Insert	36-6
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 135A, 245A	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 135A, 245A	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 135A, 245A	Termination	Solder Cup
Ingress Protection  IP65 - Dust Tight, Water Resistant  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  135A, 245A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Strain Relief  135A, 245A	Orientation	N (Normal)
Contact Finish Silver  Features Strain Relief Voltage - Rated Current Rating 135A, 245A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features Strain Relief  Voltage - Rated 50V  Current Rating 135A, 245A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 135A, 245A	Contact Finish	Silver
Current Rating 135A, 245A	Features	Strain Relief
	Voltage - Rated	50V
Report errors?	Current Rating	135A, 245A
		Report errors?

### CA3108E36-6P Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **CA3108E36-6P Payment Methods**



















### **CA3108E36-6P Shipping Methods**













If you have any question about CA3108E36-6P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com