

Heisener.com

CA3108F20-29SBF80A176A232

CA3108F20-29SBF80A176A232 Information

Part Number CA3108F20-29SBF80A176A232

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 17POS RT ANG W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3108F20-29SBF80A176A232 Specifications

Manufacturer Part Number CA3108F20-29SBF80A176A232 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 17 Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A		
Category Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 17 Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Voltage - Rated Current Rating 22A	Manufacturer Part Number	CA3108F20-29SBF80A176A232
Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 17 Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 22A	Manufacturer	ITT Cannon, LLC
Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 17 Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Package	-
Number of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Number of Positions	17
Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Shell Size - Insert	20-29
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 22A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating Aluminum Alloy, Black Zinc Cobalt Plated Gold Strain Relief 22A	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Strain Relief Voltage - Rated 50V Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Black Zinc Cobalt Plated
Voltage - Rated 50V Current Rating 22A	Contact Finish	Gold
Current Rating 22A	Features	Strain Relief
	Voltage - Rated	50V
Report errors?	Current Rating	22A
Report circles.		Report errors?

CA3108F20-29SBF80A176A232 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3108F20-29SBF80A176A232 Payment Methods



















CA3108F20-29SBF80A176A232 Shipping Methods













If you have any question about CA3108F20-29SBF80A176A232, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com