



## CA3108F32-15PB Information

Heisener.com

**Part Number** CA3108F32-15PB **Manufacturer** ITT Cannon, LLC

**Category** Connectors, Interconnects

Circular Connectors

**Description** CONN PLUG 8POS INLINE W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **CA3108F32-15PB Specifications**

Manufacturer Part NumberCA3108F32-15PBManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Male PinsNumber of Positions8Shell Size - Insert32-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating41A, 245A		
Category Circular Connectors  Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Male Pins Number of Positions 8 Shell Size - Insert 32-15 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated Solve	Manufacturer Part Number	CA3108F32-15PB
Circular ConnectorsPackage-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Male PinsNumber of Positions8Shell Size - Insert32-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-B Connector Type Plug, Male Pins Number of Positions 8 Shell Size - Insert 32-15 Shell Size, MIL -  Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-B  Connector Type Plug, Male Pins  Number of Positions 8  Shell Size - Insert 32-15  Shell Size, MIL  Mounting Type Free Hanging (In-Line), Right Angle  Termination Solder Cup  Fastening Type Reverse Bayonet Lock  Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 50V		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions8Shell Size - Insert32-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V	Package	-
Number of Positions  Shell Size - Insert  32-15  Shell Size, MIL  Mounting Type  Free Hanging (In-Line), Right Angle  Termination  Solder Cup  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  50V	Series	MIL-DTL-5015, CA-B
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line), Right Angle  Termination  Solder Cup  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Strain Relief  Voltage - Rated  32-15  August 15  August 16  Voltage - Rated	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line), Right Angle  Termination Solder Cup  Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated  50V	Number of Positions	8
Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V	Shell Size - Insert	32-15
Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V	Termination	Solder Cup
Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V	Fastening Type	Reverse Bayonet Lock
Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V	Orientation	N (Normal)
Contact Finish Silver Features Strain Relief Voltage - Rated 50V	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Strain Relief Voltage - Rated 50V	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V	Contact Finish	Silver
	Features	Strain Relief
Current Rating 41A, 245A	Voltage - Rated	50V
	Current Rating	41A, 245A
Report errors?		Report errors?

#### CA3108F32-15PB Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# CA3108F32-15PB Payment Methods





















### CA3108F32-15PB Shipping Methods













If you have any question about CA3108F32-15PB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com