



## CA3108R20-24SBF80 Information

Heisener.com

**Part Number** CA3108R20-24SBF80 **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

**Description** CONN PLUG 4 POS STRAIGHT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CA3108R20-24SBF80 Specifications

Manufacturer Part Number       CA3108R20-24SBF80         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-5015, CA-B         Connector Type       Plug, Female Sockets         Number of Positions       4         Shell Size - Insert       20-24         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line), Right Angle         Termination       Crimp         Fastening Type       Reverse Bayonet Lock         Orientation       N (Normal)         Ingress Protection       IP67 - Dust Tight, Waterproof         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       -         Voltage - Rated       50V         Current Rating       22A, 74A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert20-24Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 74A	Manufacturer Part Number	CA3108R20-24SBF80
Package-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert20-24Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 74A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 20-24 Shell Size, MIL - Crimp Mounting Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 222A, 74A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert20-24Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 74A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert20-24Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 74A	Package	-
Number of Positions4Shell Size - Insert20-24Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 74A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line), Right Angle  Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 50V Current Rating 22A, 74A	Number of Positions	4
Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 74A	Shell Size - Insert	20-24
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 74A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 74A	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 74A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 74A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver	Orientation	N (Normal)
Contact Finish Silver  Features - Voltage - Rated Current Rating 22A, 74A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 50V Current Rating 22A, 74A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A, 74A	Contact Finish	Silver
Current Rating 22A, 74A	Features	-
-	Voltage - Rated	50V
	Current Rating	22A, 74A
Report errors?		Report errors?

#### CA3108R20-24SBF80 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CA3108R20-24SBF80 Payment Methods



















## CA3108R20-24SBF80 Shipping Methods













If you have any question about CA3108R20-24SBF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com