

CA3130MZ Information

value, hersener.com

For Reference Only

Part Number CA3130MZ

ManufacturerRenesas Electronics AmericaCategoryIntegrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 15MHZ 8SOIC **Package** 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3130MZ Specifications

Manufacturer Part Number CA3130MZ Manufacturer Renesas Electronics America Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 1 Output Type - Slew Rate 30 V/μs Gain Bandwidth Product 15MHz -3db Bandwidth - Current - Input Bias 5pA Voltage - Input Offset 8mV Current - Supply 10mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 5 V ~ 16 V, ±2.5 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC		
CategoryIntegrated Circuits (ICs)Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage8-SOIC (0.154", 3.90mm Width)Series-Amplifier TypeGeneral PurposeNumber of Circuits1Output Type-Slew Rate30 V/μsGain Bandwidth Product15MHz-3db Bandwidth-Current - Input Bias5pAVoltage - Input Offset8mVCurrent - Output / Channel45mAVoltage - Supply, Single/Dual (±)5 V ~ 16 V, ±2.5 V ~ 8 VOperating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)	Manufacturer Part Number	CA3130MZ
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 1 Output Type - Slew Rate 30 V/μs Gain Bandwidth Product 15MHz -3db Bandwidth - Current - Input Bias 5pA Voltage - Input Offset 8mV Current - Supply 10mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 5 V ~ 16 V, ±2.5 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Manufacturer	Renesas Electronics America
Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 1 Output Type - Slew Rate 30 V/µs Gain Bandwidth Product 15MHz -3db Bandwidth - Current - Input Bias 5pA Voltage - Input Offset 8mV Current - Supply 10mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 5 V ~ 16 V, ±2.5 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Category	Integrated Circuits (ICs)
Series - Amplifier Type General Purpose Number of Circuits 1 Output Type - Slew Rate 30 V/µs Gain Bandwidth Product 15MHz -3db Bandwidth - Current - Input Bias 5pA Voltage - Input Offset 8mV Current - Supply 10mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 5 V ~ 16 V, ±2.5 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type General Purpose Number of Circuits 1 Output Type Slew Rate 30 V/ μ s Gain Bandwidth Product 15MHz -3db Bandwidth	Package	8-SOIC (0.154", 3.90mm Width)
Number of Circuits 1 Output Type - Slew Rate 30 V/μs Gain Bandwidth Product 15MHz -3db Bandwidth - Current - Input Bias 5pA Voltage - Input Offset 8mV Current - Supply 10mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 5 V ~ 16 V, ±2.5 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Series	-
Output Type - Slew Rate 30 V/μs Gain Bandwidth Product 15MHz -3db Bandwidth - Current - Input Bias 5pA Voltage - Input Offset 8mV Current - Supply 10mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 5 V ~ 16 V, ±2.5 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Amplifier Type	General Purpose
Slew Rate 30 V/µs Gain Bandwidth Product 15MHz -3db Bandwidth - Current - Input Bias 5pA Voltage - Input Offset 8mV Current - Supply 10mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 5 V ~ 16 V, ±2.5 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Number of Circuits	1
Gain Bandwidth Product -3db Bandwidth - Current - Input Bias 5pA Voltage - Input Offset 8mV Current - Supply 10mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 5 V ~ 16 V, ±2.5 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Output Type	-
-3db Bandwidth - Current - Input Bias 5pA Voltage - Input Offset 8mV Current - Supply 10mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 5 V ~ 16 V, ±2.5 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Slew Rate	30 V/μs
Current - Input Bias 5pA Voltage - Input Offset 8mV Current - Supply 10mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 5 V ~ 16 V, ±2.5 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Gain Bandwidth Product	15MHz
Voltage - Input Offset Current - Supply 10mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 5 V ~ 16 V, ±2.5 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	-3db Bandwidth	-
Current - Supply 10mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 5 V ~ 16 V, ±2.5 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Current - Input Bias	5pA
Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) $5 \text{ V} \sim 16 \text{ V}, \pm 2.5 \text{ V} \sim 8 \text{ V}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type Surface Mount Package / Case $8-\text{SOIC}$ (0.154", 3.90mm Width)	Voltage - Input Offset	8mV
Voltage - Supply, Single/Dual (\pm) 5 V ~ 16 V, \pm 2.5 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Current - Supply	10mA
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Current - Output / Channel	45mA
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Voltage - Supply, Single/Dual (±)	5 V ~ 16 V, ±2.5 V ~ 8 V
Package / Case 8-SOIC (0.154", 3.90mm Width)	Operating Temperature	-55°C ~ 125°C
	Mounting Type	Surface Mount
Supplier Device Package 8-SOIC	Package / Case	8-SOIC (0.154", 3.90mm Width)
	Supplier Device Package	8-SOIC
Report errors		Report errors?

CA3130MZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3130MZ Payment Methods





















CA3130MZ Shipping Methods













If you have any question about CA3130MZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com