

CA3260AE Information



For Reference Only

Part Number CA3260AE Manufacturer Intersil

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 4MHZ 8DIP **Package** 8-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3260AE Specifications

Manufacturer Part Number CA3260AE Manufacturer Intersil Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 10 V/μs Gain Bandwidth Product 4MHz -3db Bandwidth - Current - Input Bias 2pA Voltage - Input Offset 2mV Current - Supply 9mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 4 V ~ 16 V, ±2 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 10 V/μs Gain Bandwidth Product 4MHz -3db Bandwidth - Current - Input Bias 2pA Voltage - Input Offset 2mV Current - Supply 9mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 4 V ~ 16 V, ±2 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Manufacturer Part Number	CA3260AE
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 10 V/μs Gain Bandwidth Product 4MHz -3db Bandwidth - Current - Input Bias 2pA Voltage - Input Offset 2mV Current - Supply 9mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 4 V ~ 16 V, ±2 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Manufacturer	Intersil
Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 10 V/μs Gain Bandwidth Product 4MHz -3db Bandwidth - Current - Input Bias 2pA Voltage - Input Offset 2mV Current - Supply 9mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 4 V ~ 16 V, ±2 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Category	Integrated Circuits (ICs)
Series - General Purpose Number of Circuits 2 Output Type - Slew Rate 10 V/µs Gain Bandwidth Product 4MHz -3db Bandwidth - Current - Input Bias 2pA Voltage - Input Offset 2mV Current - Supply 9mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 4 V ~ 16 V, ±2 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type Number of Circuits 2 Output Type - Slew Rate 10 V/µs Gain Bandwidth Product -3db Bandwidth - Current - Input Bias Voltage - Input Offset 2mV Current - Supply 9mA Current - Output / Channel Voltage - Supply, Single/Dual (±) 4 V ~ 16 V, ±2 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Package	8-DIP (0.300", 7.62mm)
Number of Circuits 2 Output Type - Slew Rate 10 V/μs Gain Bandwidth Product 4MHz -3db Bandwidth - Current - Input Bias 2pA Voltage - Input Offset 2mV Current - Supply 9mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 4 V ~ 16 V, ±2 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Series	-
Output Type Slew Rate 10 V/µs Gain Bandwidth Product -3db Bandwidth - Current - Input Bias 2pA Voltage - Input Offset Current - Supply 9mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 4 V ~ 16 V, ±2 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Amplifier Type	General Purpose
Slew Rate Gain Bandwidth Product -3db Bandwidth - Current - Input Bias Voltage - Input Offset Current - Supply 9mA Current - Output / Channel Voltage - Supply, Single/Dual (±) 4 V ~ 16 V, ±2 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Number of Circuits	2
Gain Bandwidth Product -3db Bandwidth - Current - Input Bias 2pA Voltage - Input Offset 2mV Current - Supply 9mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 4 V ~ 16 V, ±2 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Output Type	-
-3db Bandwidth - Current - Input Bias 2pA Voltage - Input Offset 2mV Current - Supply 9mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 4 V ~ 16 V, ±2 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Slew Rate	10 V/μs
Current - Input Bias 2pA Voltage - Input Offset 2mV Current - Supply 9mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 4 V ~ 16 V, ±2 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Gain Bandwidth Product	4MHz
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	-3db Bandwidth	-
Current - Supply 9mA Current - Output / Channel 45mA Voltage - Supply, Single/Dual (±) 4 V ~ 16 V, ±2 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Current - Input Bias	2pA
Current - Output / Channel 45mA Voltage - Supply, Single/Dual (\pm) 4 V ~ 16 V, \pm 2 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Voltage - Input Offset	2mV
Voltage - Supply, Single/Dual (\pm) 4 V ~ 16 V, \pm 2 V ~ 8 V Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Current - Supply	9mA
Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Current - Output / Channel	45mA
Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Voltage - Supply, Single/Dual (±)	4 V ~ 16 V, ±2 V ~ 8 V
Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Operating Temperature	-55°C ~ 125°C
Supplier Device Package 8-PDIP	Mounting Type	Through Hole
	Package / Case	8-DIP (0.300", 7.62mm)
	Supplier Device Package	8-PDIP
Report errors's		Report errors?

CA3260AE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3260AE Payment Methods





















CA3260AE Shipping Methods













If you have any question about CA3260AE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com