

CA5075330R0KR05

a Quote

CA5075330R0KR05 Information

Heisener.com	Part Number	CA5075330R0KR05	
	Manufacturer	Vishay Dale	
	Category	Resistors Through Hole Resistors	
	Description	RES 330 OHM 3.75W 10% AXIAL	- i266
	Package	Axial	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CA5075330R0KR05 Specifications

Manufacturer Part Number CA5075330R0KR05 Manufacturer Vishay Dale Category Resistors Through Hole Resistors Axial Package Axial Series CA Resistance 330 Ohms Tolerance ±10% Power (Watts) 3.75W Composition Wirewound Features - Tolerance Coefficient ±300pm/°C Operating Temperature -65°C ~ 275°C Package / Case Axial Size / Dimension 0.170° Dia x 0.825° L (4.32mm x 20.96mm) Height - Seated (Max) - Number of Terminations 2 Failure Rate -			
CategoryReformCategoryThrough Hole ResistorsPackageAxialPackageCAResistance330 OhmsTolerance±10%Power (Watts)3.75WCompositionWirewoundFeatures-Temperature Coefficient±300pm/°COperating Temperature-65°C ~275°CPackage / CaseAxialSupplic Device Package0.170° Dia x 0.825° L (4.32mm x 20.96mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Manufacturer Part Number	CA5075330R0KR05	
Through Hole ResistorsPackageAxialSeriesCAResistance330 OhmsTolerance±10%Power (Watts)3.75WCompositionWirewoundFeatures-Temperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.170" Dia x 0.825" L (4.32mm x 20.96mm)Height - Seated (Max)2Failure Rate-	Manufacturer	Vishay Dale	
PackageAxiaSeriesCAResistance330 OhmsTolerance±10%Power (Wats)3.75WCompositionWirewoundFeatures-Temperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseAxialSupplier Device Package0.170° Dia x 0.825° L (4.32mm x 20.96mm)Height - Seated (Max)2Aumber of Terminations2Failure Rate-	Category	Resistors	
Series CA Resistance 330 Ohms Tolerance ±10% Power (Watts) 3.75W Composition Wirewound Features - Temperature Coefficient ±300pm/°C Operating Temperature -65°C ~ 275°C Package / Case Axial Supplier Device Package 0.170° Dia x 0.825° L (4.32mm x 20.96mm) Height - Seated (Max) 2 Number of Terminations 2 Failure Rate -		Through Hole Resistors	
Resistance330 OhmsTolerance±10%Power (Watts)3.75WCompositionWirewoundFeatures-Temperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseAxialSupplier Device Package0.170" Dia x 0.825" L (4.32mm x 20.96mm)Height - Seated (Max)-Aumber of Terminations2Failure Rate-	Package	Axial	
Tolerance±10%Power (Watts)3.75WCompositionWirewoundFeatures-Temperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseAxialSupplier Device Package0.170" Dia x 0.825" L (4.32mm x 20.96mm)Size / Dimension-Height - Seated (Max)2Number of Terminations2Failure Rate-	Series	CA	
Power (Watts)3.75WCompositionWirewoundFeatures-Temperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.170" Dia x 0.825" L (4.32mm x 20.96mm)Height - Seated (Max)-Sunber of Terminations2Failure Rate-	Resistance	330 Ohms	
CompositionWirewoundFeatures-Temperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.170° Dia x 0.825° L (4.32mm x 20.96mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Tolerance	$\pm 10\%$	
Features-Features=300ppm/°COperating Temperature=65°C ~ 275°CPackage / CaseAxialSupplier Device Package0.170" Dia x 0.825" L (4.32mm x 20.96mm)Height - Seated (Max)=Number of Terminations2Failure Rate-	Power (Watts)	3.75W	
Temperature Coefficient±300pm/°COperating Temperature-65°C ~ 275°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.170" Dia x 0.825" L (4.32mm x 20.96mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Composition	Wirewound	
Operating Temperature-65°C ~ 275°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.170" Dia x 0.825" L (4.32mm x 20.96mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Features	-	
Package / CaseAxialSupplier Device PackageAxialSize / Dimension0.170" Dia x 0.825" L (4.32mm x 20.96mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Temperature Coefficient	±300ppm/°C	
Supplier Device PackageAxialSize / Dimension0.170" Dia x 0.825" L (4.32mm x 20.96mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Operating Temperature	-65°C ~ 275°C	
Number of Terminations0.170" Dia x 0.825" L (4.32mm x 20.96mm)Failure Rate-Output-State- <td>Package / Case</td> <td>Axial</td> <td></td>	Package / Case	Axial	
Height - Seated (Max)-Number of Terminations2Failure Rate-	Supplier Device Package	Axial	
Number of Terminations2Failure Rate-	Size / Dimension	0.170" Dia x 0.825" L (4.32mm x 20.96mm)	
Failure Rate -	Height - Seated (Max)	-	
	Number of Terminations	2	
Report errors?	Failure Rate	-	
1		Report en	rors?

CA5075330R0KR05 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CA5075330R0KR05 Payment Methods



If you have any question about CA5075330R0KR05, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com