

CAF94810(IDD5250-RT12) Information

Heisener.com	CAF94810(IDD5250-RT12) Laird Technologies IAS RF/IF and RFID RF Antennas ANT TERRACE DIV 5DBI 12"RPTNC X2 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CAF94810(IDD5250-RT12) Specifications

Manufacturer Laird Technologies IAS Category RF/IF and RFID RE Antennas RF Antennas Package - Series Terrace Diversity? Frequency Group SHF (f > 4 GHz) Frequency Center/Band) 5GHz Frequency Range 4.9GHz ~ 6GHz Antenna Type Module Number of Bands 1 VSWR 2 Gain 5dBi Power - Max 50W Features - Termination Cable (305mm) - RP-TNC (2) Ingress Protection - Mounting Type Bracket Mount Height (Max) 1.063" (27.00mm) Applications -		
CategoryRF/IF and RFID RF AntennasPackage-SeriesTerrace Diversity?Frequency GroupSHF (f > 4 GHz)Frequency Center/Band)5GHzFrequency Range4.9GHz ~ 6GHzAntenna TypeModuleNumber of Bands1VSWR2Return Loss-Gain5GHzPower - Max50WFeatures-TerminationCable (305mm) - RP-TNC (2)Ingress Protection-Mounting TypeBracket MountHeight (Max)1.063" (27.00mm)Applications-	Manufacturer Part Number	CAF94810(IDD5250-RT12)
RF AntennasPackage-SeriesTerrace Diversity?Frequency GroupSHF (f > 4 GHz)Frequency Center/Band)SGHzFrequency Range4.9GHz ~ 6GHzAntenna TypeModuleNumber of Bands1VSWR2Return Loss-Gain5dBiPower - Max50WFeatures-TerminationCable (305mm) - RP-TNC (2)Ingress Protection-Mounting TypeBracket MountHeight (Max)1.063" (27.00mm)Applications-	Manufacturer	Laird Technologies IAS
Package-SeriesTerrace Diversity?Frequency GroupSHF (f > 4 GHz)Frequency Center/Band)5GHzFrequency Range4.9GHz ~ 6GHzAntenna TypeModuleNumber of Bands1VSWR2Return Loss-Gain5dBiPower - Max50WFeatures-TerminationCable (305mn) - RP-TNC (2)Ingress Protection-Mounting TypeBracket MountHeight (Max).Applications.	Category	RF/IF and RFID
Series Terrace Diversity? Frequency Group SHF (f > 4 GHz) Frequency (Center/Band) SGHz Frequency Range 4.9GHz ~ 6GHz Antenna Type Module Number of Bands 1 VSWR 2 Return Loss - Gain 5dBi Power - Max 50W Features - Termination Cable (305mm) - RP-TNC (2) Ingress Protection - Mounting Type Bracket Mount Height (Max) 1.063" (27.00mm) Applications -		RF Antennas
Frequency Group SHF (f > 4 GHz) Frequency (Center/Band) 5GHz Frequency Range 4.9GHz ~ 6GHz Antenna Type Module Number of Bands 1 VSWR 2 Return Loss - Gain 5dBi Power - Max 50W Features - Termination Cable (305mm) - RP-TNC (2) Ingress Protection - Mounting Type Bracket Mount Height (Max) . Applications .	Package	-
Frequency (Center/Band)5GHzFrequency Range4.9GHz ~ 6GHzAntenna TypeModuleNumber of Bands1VSWR2Return Loss-Gain5dBiPower - Max50WFeatures-TerminationCable (305mm) - RP-TNC (2)Ingress Protection-Mounting TypeBracket MountHeight (Max)1.063" (27.00mm)Applications-	Series	Terrace Diversity?
Frequency Range4.9GHz ~ 6GHzAntenna TypeModuleNumber of Bands1VSWR2Return Loss-Gain5dBiPower - Max50WFeatures-TerminationCable (305mm) - RP-TNC (2)Ingress Protection-Mounting TypeBracket MountHeight (Max)1.063" (27.00mm)Applications-	Frequency Group	SHF (f > 4 GHz)
Antenna TypeModuleNumber of Bands1Number of Bands2VSWR2Return Loss-Gain5dBiPower - Max50WFeatures-TerminationCable (305mm) - RP-TNC (2)Ingress Protection-Mounting TypeBracket MountHeight (Max)1.063" (27.00mm)Applications-	Frequency (Center/Band)	5GHz
Number of Bands1Number of Bands2VSWR2Return Loss-Gain5dBiPower - Max50WFeatures-TerminationCable (305mm) - RP-TNC (2)Ingress Protection-Mounting TypeBracket MountHeight (Max)1.063" (27.00mm)Applications-	Frequency Range	4.9GHz ~ 6GHz
VSWR2Return Loss-Gain5dBiPower - Max50WPower - Max-Features-TerminationCable (305mm) - RP-TNC (2)Ingress Protection-Mounting TypeBracket MountHeight (Max)1.063" (27.00mm)Applications-	Antenna Type	Module
Return Loss-Gain5dBiPower - Max50WFeatures-TerminationCable (305mm) - RP-TNC (2)Ingress Protection-Mounting TypeBracket MountHeight (Max)1.063" (27.00mm)Applications-	Number of Bands	1
Gain5dBiPower - Max50WFeatures-TerminationCable (305mm) - RP-TNC (2)Ingress Protection-Mounting TypeBracket MountHeight (Max)1.063" (27.00mm)Applications-	VSWR	2
Power - Max50WFeatures-TerminationCable (305mm) - RP-TNC (2)Ingress Protection-Mounting TypeBracket MountHeight (Max)1.063" (27.00mm)Applications-	Return Loss	-
Features-TerminationCable (305mm) - RP-TNC (2)Ingress Protection-Mounting TypeBracket MountHeight (Max)1.063" (27.00mm)Applications-	Gain	5dBi
TerminationCable (305mm) - RP-TNC (2)Ingress Protection-Mounting TypeBracket MountHeight (Max)1.063" (27.00mm)Applications-	Power - Max	50W
Ingress Protection - Mounting Type Bracket Mount Height (Max) 1.063" (27.00mm) Applications -	Features	-
Mounting TypeBracket MountHeight (Max)1.063" (27.00mm)Applications-	Termination	Cable (305mm) - RP-TNC (2)
Height (Max)1.063" (27.00mm)Applications-	Ingress Protection	-
Applications -	Mounting Type	Bracket Mount
	Height (Max)	1.063" (27.00mm)
Report errors?	Applications	-
		Report errors?

CAF94810(IDD5250-RT12) Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CAF94810(IDD5250-RT12) Payment Methods



If you have any question about CAF94810(IDD5250-RT12), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com