



CAT16-2000F4LF Information



For Reference Only

Part Number CAT16-2000F4LF

Manufacturer Bourns Inc.
Category Resistors

Resistor Networks, Arrays

Description RES ARRAY 4 RES 200 OHM 1206

Package 1206 (3216 Metric), Concave, Long Side Terminals

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CAT16-2000F4LF Specifications

Manufacturer Part Number CAT16-2000F4LF Manufacturer Bourns Inc. Category Resistors Package 1206 (3216 Metric), Concave, Long Side Terminals Series CAT16 Circuit Type Isolated Resistance (Ohms) 200 Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)		
Category Resistors Resistor Networks, Arrays Package 1206 (3216 Metric), Concave, Long Side Terminals Series CAT16 Circuit Type Isolated Resistance (Ohms) 200 Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)	Manufacturer Part Number	CAT16-2000F4LF
Resistor Networks, Arrays Package 1206 (3216 Metric), Concave, Long Side Terminals Series CAT16 Circuit Type Isolated Resistance (Ohms) 200 Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)	Manufacturer	Bourns Inc.
Package 1206 (3216 Metric), Concave, Long Side Terminals Series CAT16 Circuit Type Isolated Resistance (Ohms) 200 Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)	Category	Resistors
SeriesCAT16Circuit TypeIsolatedResistance (Ohms)200Tolerance±1%Number of Resistors4Number of Pins8Power Per Element62.5mWTemperature Coefficient±200ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeSurface MountPackage / Case1206 (3216 Metric), Concave, Long Side TerminalsSupplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.024" (0.60mm)		Resistor Networks, Arrays
Circuit Type Isolated Resistance (Ohms) 200 Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)	Package	1206 (3216 Metric), Concave, Long Side Terminals
Resistance (Ohms) 200 Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)	Series	CAT16
Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)	Circuit Type	Isolated
Number of Resistors A Number of Pins B Cover Per Element 62.5mW Temperature Coefficient -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)	Resistance (Ohms)	200
Number of Pins Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)	Tolerance	±1%
Power Per Element Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)	Number of Resistors	4
Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)	Number of Pins	8
Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)	Power Per Element	62.5mW
Applications - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)	Temperature Coefficient	±200ppm/°C
Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)	Operating Temperature	-55°C ~ 125°C
Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)	Applications	-
Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)	Mounting Type	Surface Mount
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.024" (0.60mm)	Package / Case	1206 (3216 Metric), Concave, Long Side Terminals
Height - Seated (Max) 0.024" (0.60mm)	Supplier Device Package	1206
	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Report errors?	Height - Seated (Max)	0.024" (0.60mm)
Report offors.		Report errors?

CAT16-2000F4LF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CAT16-2000F4LF Payment Methods



















CAT16-2000F4LF Shipping Methods













If you have any question about CAT16-2000F4LF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com