



### **CAT16-5R1J4GLF Information**

Part Number CAT16-5R1J4GLF

Manufacturer Bourns Inc.
Category Resistors

Resistor Networks, Arrays

**Description** RES ARRAY 4 RES 5.1 OHM 1206

Package 1206 (3216 Metric), Concave, Long Side Terminals

For the pricing/inventory/lead time, please contact

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **CAT16-5R1J4GLF Specifications**

Manufacturer Part NumberCAT16-5R1J4GLFManufacturerBourns Inc.CategoryResistorsPackage1206 (3216 Metric), Concave, Long Side TerminalsSeriesCAT16Circuit TypeIsolatedResistance (Ohms)5.1Tolerance±5%Number of Resistors4Number of Pins8Power Per Element62.5mWTemperature Coefficient±200ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeSurface MountPackage / Case1206 (3216 Metric), Concave, Long Side TerminalsSupplier Device Package1206Size / Dimension0.126" L x 0.061" W (3.20mm x 1.55mm)Height - Seated (Max)0.024" (0.60mm)		
Category         Resistors           Resistor Networks, Arrays           Package         1206 (3216 Metric), Concave, Long Side Terminals           Series         CAT16           Circuit Type         Isolated           Resistance (Ohms)         5.1           Tolerance         ±5%           Number of Resistors         4           Number of Pins         8           Power Per Element         62.5mW           Temperature Coefficient         ±200ppm/°C           Operating Temperature         -55°C ~ 125°C           Applications         -           Mounting Type         Surface Mount           Package / Case         1206 (3216 Metric), Concave, Long Side Terminals           Supplier Device Package         1206           Size / Dimension         0.126" L x 0.061" W (3.20mm x 1.55mm)           Height - Seated (Max)         0.024" (0.60mm)	Manufacturer Part Number	CAT16-5R1J4GLF
Resistor Networks, Arrays           Package         1206 (3216 Metric), Concave, Long Side Terminals           Series         CAT16           Circuit Type         Isolated           Resistance (Ohms)         5.1           Tolerance         ±5%           Number of Resistors         4           Number of Pins         8           Power Per Element         62.5mW           Temperature Coefficient         ±200ppm/°C           Operating Temperature         -55°C ~ 125°C           Applications         -           Mounting Type         Surface Mount           Package / Case         1206 (3216 Metric), Concave, Long Side Terminals           Supplier Device Package         1206           Size / Dimension         0.126" L x 0.061" W (3.20mm x 1.55mm)           Height - Seated (Max)         0.024" (0.60mm)	Manufacturer	Bourns Inc.
Package         1206 (3216 Metric), Concave, Long Side Terminals           Series         CAT16           Circuit Type         Isolated           Resistance (Ohms)         5.1           Tolerance         ±5%           Number of Resistors         4           Number of Pins         8           Power Per Element         62.5mW           Temperature Coefficient         ±200ppm/°C           Operating Temperature         -55°C ~ 125°C           Applications         -           Mounting Type         Surface Mount           Package / Case         1206 (3216 Metric), Concave, Long Side Terminals           Supplier Device Package         1206           Size / Dimension         0.126" L x 0.061" W (3.20mm x 1.55mm)           Height - Seated (Max)         0.024" (0.60mm)	Category	Resistors
SeriesCAT16Circuit TypeIsolatedResistance (Ohms)5.1Tolerance±5%Number of Resistors4Number of Pins8Power Per Element62.5mWTemperature Coefficient±200ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeSurface MountPackage / Case1206 (3216 Metric), Concave, Long Side TerminalsSupplier Device Package1206Size / Dimension0.126" L x 0.061" W (3.20mm x 1.55mm)Height - Seated (Max)0.024" (0.60mm)		Resistor Networks, Arrays
Circuit Type         Isolated           Resistance (Ohms)         5.1           Tolerance         ±5%           Number of Resistors         4           Number of Pins         8           Power Per Element         62.5mW           Temperature Coefficient         ±200ppm/°C           Operating Temperature         -55°C ~ 125°C           Applications         -           Mounting Type         Surface Mount           Package / Case         1206 (3216 Metric), Concave, Long Side Terminals           Supplier Device Package         1206           Size / Dimension         0.126" L x 0.061" W (3.20mm x 1.55mm)           Height - Seated (Max)         0.024" (0.60mm)	Package	1206 (3216 Metric), Concave, Long Side Terminals
Resistance (Ohms)       5.1         Tolerance       ±5%         Number of Resistors       4         Number of Pins       8         Power Per Element       62.5mW         Temperature Coefficient       ±200ppm/°C         Operating Temperature       -55°C ~ 125°C         Applications       -         Mounting Type       Surface Mount         Package / Case       1206 (3216 Metric), Concave, Long Side Terminals         Supplier Device Package       1206         Size / Dimension       0.126" L x 0.061" W (3.20mm x 1.55mm)         Height - Seated (Max)       0.024" (0.60mm)	Series	CAT16
Tolerance ±5%  Number of Resistors 4  Number of Pins 8  Power Per Element 62.5mW  Temperature Coefficient ±200ppm/°C  Operating Temperature -55°C ~ 125°C  Applications -  Mounting Type Surface Mount  Package / Case 1206 (3216 Metric), Concave, Long Side Terminals  Supplier Device Package 1206  Size / Dimension 0.126" L x 0.061" W (3.20mm x 1.55mm)  Height - Seated (Max) 0.024" (0.60mm)	Circuit Type	Isolated
Number of Resistors  A Number of Pins  B  Rower Per Element  62.5mW  Temperature Coefficient  -55°C ~ 125°C  Applications  -  Mounting Type  Surface Mount  Package / Case  1206 (3216 Metric), Concave, Long Side Terminals  Supplier Device Package  Size / Dimension  0.126" L x 0.061" W (3.20mm x 1.55mm)  Height - Seated (Max)  0.024" (0.60mm)	Resistance (Ohms)	5.1
Number of Pins  Power Per Element  62.5mW  Temperature Coefficient  ±200ppm/°C  Operating Temperature  -55°C ~ 125°C  Applications  -  Mounting Type  Surface Mount  Package / Case  1206 (3216 Metric), Concave, Long Side Terminals  Supplier Device Package  1206  Size / Dimension  0.126" L x 0.061" W (3.20mm x 1.55mm)  Height - Seated (Max)  0.024" (0.60mm)	Tolerance	±5%
Power Per Element  Temperature Coefficient  ±200ppm/°C  Operating Temperature  -55°C ~ 125°C  Applications  -  Mounting Type  Surface Mount  Package / Case  1206 (3216 Metric), Concave, Long Side Terminals  Supplier Device Package  1206  Size / Dimension  0.126" L x 0.061" W (3.20mm x 1.55mm)  Height - Seated (Max)  0.024" (0.60mm)	Number of Resistors	4
Temperature Coefficient ±200ppm/°C  Operating Temperature -55°C ~ 125°C  Applications -  Mounting Type Surface Mount  Package / Case 1206 (3216 Metric), Concave, Long Side Terminals  Supplier Device Package 1206  Size / Dimension 0.126" L x 0.061" W (3.20mm x 1.55mm)  Height - Seated (Max) 0.024" (0.60mm)	Number of Pins	8
Operating Temperature  -55°C ~ 125°C  Applications  -  Mounting Type  Surface Mount  Package / Case  1206 (3216 Metric), Concave, Long Side Terminals  Supplier Device Package  1206  Size / Dimension  0.126" L x 0.061" W (3.20mm x 1.55mm)  Height - Seated (Max)  0.024" (0.60mm)	Power Per Element	62.5mW
Applications - Mounting Type Surface Mount  Package / Case 1206 (3216 Metric), Concave, Long Side Terminals  Supplier Device Package 1206  Size / Dimension 0.126" L x 0.061" W (3.20mm x 1.55mm)  Height - Seated (Max) 0.024" (0.60mm)	Temperature Coefficient	±200ppm/°C
Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Supplier Device Package 1206 Size / Dimension 0.126" L x 0.061" W (3.20mm x 1.55mm) Height - Seated (Max) 0.024" (0.60mm)	Operating Temperature	-55°C ~ 125°C
Package / Case 1206 (3216 Metric), Concave, Long Side Terminals  Supplier Device Package 1206  Size / Dimension 0.126" L x 0.061" W (3.20mm x 1.55mm)  Height - Seated (Max) 0.024" (0.60mm)	Applications	-
Supplier Device Package         1206           Size / Dimension         0.126" L x 0.061" W (3.20mm x 1.55mm)           Height - Seated (Max)         0.024" (0.60mm)	Mounting Type	Surface Mount
Size / Dimension       0.126" L x 0.061" W (3.20mm x 1.55mm)         Height - Seated (Max)       0.024" (0.60mm)	Package / Case	1206 (3216 Metric), Concave, Long Side Terminals
Height - Seated (Max) 0.024" (0.60mm)	Supplier Device Package	1206
	Size / Dimension	0.126" L x 0.061" W (3.20mm x 1.55mm)
Report errors?	Height - Seated (Max)	0.024" (0.60mm)
		Report errors?

### **CAT16-5R1J4GLF Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **CAT16-5R1J4GLF Payment Methods**



















## **CAT16-5R1J4GLF Shipping Methods**













If you have any question about CAT16-5R1J4GLF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com