

CB1-P-24V Information



For Reference Only

Part Number CB1-P-24V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY AUTOMOTIVE SPDT 20A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CB1-P-24V Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Power Relays, Over 2 Amps Package - Series CB Relay Type Automotive Coil Type Non Latching Coil Current 75mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 15ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesCBRelay TypeAutomotiveCoil TypeNon LatchingCoil Current75mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage28VDC - NomTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time15msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	CB1-P-24V
Package - Series CB Relay Type Automotive Coil Type Non Latching Coil Current 75mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 15ms Features Sealed - Fully Mounting Type Through Hole Termination Style Permination Style	Manufacturer	Panasonic Electric Works
Package-SeriesCBRelay TypeAutomotiveCoil TypeNon LatchingCoil Current75mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage28VDC - NomTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time15msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesCBRelay TypeAutomotiveCoil TypeNon LatchingCoil Current75mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage28VDC - NomTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time15msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeAutomotiveCoil TypeNon LatchingCoil Current75mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage28VDC - NomTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time15msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current75mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage28VDC - NomTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time15msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	CB
Coil Current 75mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 15ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	Automotive
Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 15ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 20A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 15ms Release Time 15ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Current	75mA
Contact Rating (Current) Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 15ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Voltage	24VDC
Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 15ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 15ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	20A
Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features Sealed - Fully Mounting Type Through Hole Termination Style 2.4 VDC 15ms PC Pin	Switching Voltage	28VDC - Nom
Operate Time15msRelease Time15msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	14 VDC
Release Time 15ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	2.4 VDC
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	15ms
Termination Style PC Pin	Features	Sealed - Fully
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
•		Report errors?

CB1-P-24V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CB1-P-24V Payment Methods





















CB1-P-24V Shipping Methods













If you have any question about CB1-P-24V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com