

CB172E0225KBC

est a Quote

CB172E0225KBC Information

Heisener.com Betarlarvor statuter	Part Number	CB172E0225KBC	
	Manufacturer	AVX Corporation	
	Category	Capacitors Film Capacitors	Ē
	Description	CAP FILM 2.2UF 10% 100VDC 5040	- 53
	Package	5040 (127102 Metric)	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	R

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CB172E0225KBC Specifications

Manufacturer Part Number CB172E0225KBC Manufacturer AVX Corporation Category Capacitors Film Capacitors Film Capacitors Package 5040 (127102 Metric) Series CB Capacitance 2.2µF Yoltage Rating - AC 63V Voltage Rating - DC 100V Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked Strig Capacitance - Operating Temperature 5040 (127102 Metric) Sundacturer Part Material Sundacturer Part Metallized - Stacked Strig Capacitance - Operating Temperature - Mounting Type Surface Mount Stacked (Max) - Stacked (Max) - Termination Solder Pads Lead Spacing - Applications General Purpose Lead Spacing - Applications General Purpose			
CategoryCapacitorsFilm CapacitorsPackage5040 (127102 Metric)SeriesCBCapacitance2.2µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedSSR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case5040 (127102 Metric)Size / Dimension0.503° L x 0.402° W (12.80mm x 10.20mm)Height - Seated (Max)-TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Manufacturer Part Number	CB172E0225KBC	
Filn CapacitorsPackage5040 (127102 Metric)SeriesCBCapacitance2.2µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case5040 (127102 Metric)Size / Dimension.503" L x 0.402" W (12.80mm x 10.20mm)Height - Seated (Max)-TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Manufacturer	AVX Corporation	
Package5040 (127102 Metric)SeriesCBCapacitance2.2µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature55°C ~ 125°CMounting TypeSuface MountPackage / Case5040 (127102 Metric)Size / Dimension.503° L x 0.402° W (12.80mm x 10.20mm)Height - Seated (Max)-Lead Spacing.ApplicationsGeneral PurposeFeatures.	Category	Capacitors	
SeriesCBCapacitance2.2µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSufface MountPackage / Case5040 (127102 Metric)Size / Dimension.503" L x 0.402" W (12.80mm x 10.20mm)Height - Seated (Max)-FerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-		Film Capacitors	
Capacitance2.2µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case5040 (127102 Metric)Size / Dimension-Height - Seated (Max)-Lead SpacingSolder PadsLead SpacingGeneral PurposeFeatures-Features-	Package	5040 (127102 Metric)	
Tolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case5040 (127102 Metric)Size / Dimension0.503" L x 0.402" W (12.80mm x 10.20mm)Height - Seated (Max)-TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Series	СВ	
Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case5040 (127102 Metric)Size / Dimension0.503" L x 0.402" W (12.80mm x 10.20mm)Height - Seated (Max)-TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Capacitance	2.2µF	
Voltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case5040 (127102 Metric)Size / Dimension0.503" L x 0.402" W (12.80mm x 10.20mm)Height - Seated (Max)-TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Tolerance	±10%	
Dielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case5040 (127102 Metric)Size / Dimension0.503" L x 0.402" W (12.80mm x 10.20mm)Height - Seated (Max)-TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	63V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case5040 (127102 Metric)Size / Dimension0.503" L x 0.402" W (12.80mm x 10.20mm)Height - Seated (Max)-TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	100V	
Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case5040 (127102 Metric)Size / Dimension0.503" L x 0.402" W (12.80mm x 10.20mm)Height - Seated (Max)-TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked	
Mounting TypeSurface MountPackage / Case5040 (127102 Metric)Size / Dimension0.503" L x 0.402" W (12.80mm x 10.20mm)Height - Seated (Max)-TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-	
Package / Case5040 (127102 Metric)Size / Dimension0.503" L x 0.402" W (12.80mm x 10.20mm)Height - Seated (Max)-TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 125°C	
Size / Dimension0.503" L x 0.402" W (12.80mm x 10.20mm)Height - Seated (Max)-TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Mounting Type	Surface Mount	
Height - Seated (Max)-TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package / Case	5040 (127102 Metric)	
TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.503" L x 0.402" W (12.80mm x 10.20mm)	
Lead Spacing-ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	-	
ApplicationsGeneral PurposeFeatures-	Termination	Solder Pads	
Features -	Lead Spacing	-	
	Applications	General Purpose	
Report errors?	Features	-	
			Report errors?

CB172E0225KBC Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CB172E0225KBC Payment Methods



CB172E0225KBC Shipping Methods



If you have any question about CB172E0225KBC, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com