



CB1F-D-SM-24V Information



For Reference Only

Part Number CB1F-D-SM-24V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY AUTOMOTIVE SPDT 20A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CB1F-D-SM-24V Specifications

Manufacturer Part NumberCB1F-D-SM-24VManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesCBRelay TypeAutomotiveCoil TypeNon LatchingCoil Current75mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage28VDC - NomTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time-FeaturesDiode, Sealed - Flux ProtectionMounting TypeChassis MountTermination StyleQuick Connect - 0.250" (6.3mm)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesCBRelay TypeAutomotiveCoil TypeNon LatchingCoil Current75mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage28VDC - NomTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time-FeaturesDiode, Sealed - Flux ProtectionMounting TypeChassis MountTermination StyleQuick Connect - 0.250" (6.3mm)	Manufacturer Part Number	CB1F-D-SM-24V
Package - CB Relay Type Automotive Coil Type Non Latching Coil Current 75mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time Features Diode, Sealed - Flux Protection Mounting Type Chassis Mount Termination Style QCB	Manufacturer	Panasonic Electric Works
Package - CB Relay Type Automotive Coil Type Non Latching Coil Current 75mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time - Diode, Sealed - Flux Protection Mounting Type Chassis Mount Termination Style QUICK Connect - 0.250" (6.3mm)	Category	Relays
SeriesCBRelay TypeAutomotiveCoil TypeNon LatchingCoil Current75mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage28VDC - NomTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time-FeaturesDiode, Sealed - Flux ProtectionMounting TypeChassis MountTermination StyleQuick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 75mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time - Features Diode, Sealed - Flux Protection Mounting Type Chassis Mount Termination Style Automotive Au	Package	-
Coil Type Non Latching Coil Current 75mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time - Features Diode, Sealed - Flux Protection Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Series	СВ
Coil Current 75mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time - Features Diode, Sealed - Flux Protection Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Relay Type	Automotive
Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time - Features Diode, Sealed - Flux Protection Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 20A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time - Features Diode, Sealed - Flux Protection Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Coil Current	75mA
Contact Rating (Current) Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) Operate Time 15ms Release Time - Features Diode, Sealed - Flux Protection Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Coil Voltage	24VDC
Switching Voltage Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) Operate Time 15ms Release Time - Features Diode, Sealed - Flux Protection Mounting Type Chassis Mount Termination Style 28VDC - Nom 14 VDC 2.4 VDC 0perate Time 15ms - Chassis Mount Quick Connect - 0.250" (6.3mm)	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time - Features Diode, Sealed - Flux Protection Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	20A
Turn Off Voltage (Min) Operate Time 15ms Release Time - Features Diode, Sealed - Flux Protection Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Switching Voltage	28VDC - Nom
Operate Time 15ms Release Time - Features Diode, Sealed - Flux Protection Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Turn On Voltage (Max)	14 VDC
Release Time - Diode, Sealed - Flux Protection Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	2.4 VDC
Features Diode, Sealed - Flux Protection Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Operate Time	15ms
Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Release Time	-
Termination Style Quick Connect - 0.250" (6.3mm)	Features	Diode, Sealed - Flux Protection
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Quick Connect - 0.250" (6.3mm)
		Report errors?

CB1F-D-SM-24V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CB1F-D-SM-24V Payment Methods



















CB1F-D-SM-24V Shipping Methods













If you have any question about CB1F-D-SM-24V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com