

# CD17FD331JO3

## **CD17FD331JO3 Information**



### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **CD17FD331JO3 Specifications**

ManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsMica and PTFE CapacitorsMica and PTFE CapacitorsPackageRadialSeriesCD17Capacitance330pFTolerance±5%Voltage - Rated500VDielectric MaterialMicaOperating Temperature-55°C ~ 150°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.232" (5.90mm)FeaturesRF, High Q, Low LossSize / Dimension0.469" L x 0.209" W (11.90mm x 5.30mm)Height - Seated (Max)0.390" (9.90mm)		
CategoryCapacitorsMica and PTFE CapacitorsPackageRadialPackageCD17Capacitance330pFTolerance±5%Voltage - Rated500VDielectric MaterialMicaOperating Temperature-55°C ~ 150°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.232" (5.90mm)FeaturesRF, High Q, Low LossSize / Dimension0.390" (9.90mm)	Manufacturer Part Number	CD17FD331JO3
Mica and PTFE CapacitorsPackageRadialSeriesCD17Capacitance330pFTolerance±5%Voltage - Rated500VDielectric MaterialMicaOperating Temperature-55°C ~ 150°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.232" (5.90mm)FeaturesRF, High Q, Low LossSize / Dimension0.469" L x 0.209" W (11.90mm x 5.30mm)Height - Seated (Max)0.390" (9.90mm)	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadialPackageRadialSeriesCD17Capacitance330pFTolerance±5%Voltage - Rated500VDielectric MaterialMicaOperating Temperature-55°C ~ 150°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.232" (5.90mm)FeaturesRF, High Q, Low LossSize / Dimension0.469" L x 0.209" W (11.90mm x 5.30mm)Height - Seated (Max)0.390" (9.90mm)	Category	Capacitors
SeriesCD17Capacitance330pFTolerance±5%Voltage - Rated500VDielectric MaterialMicaOperating Temperature-55°C ~ 150°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.232" (5.90mm)FeaturesRF, High Q, Low LossSize / Dimension0.469" L x 0.209" W (11.90mm x 5.30mm)Height - Seated (Max)0.390" (9.90mm)		Mica and PTFE Capacitors
Capacitance330pFTolerance±5%Voltage - Rated500VDielectric MaterialMicaOperating Temperature-55°C ~ 150°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.232" (5.90mm)FeaturesRF, High Q, Low LossSize / Dimension0.469" L x 0.209" W (11.90mm x 5.30mm)Height - Seated (Max)0.390" (9.90mm)	Package	Radial
Tolerance±5%Voltage - Rated500VDielectric MaterialMicaOperating Temperature-55°C ~ 150°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.232" (5.90mm)FeaturesRF, High Q, Low LossSize / Dimension0.469" L x 0.209" W (11.90mm x 5.30mm)Height - Seated (Max)0.390" (9.90mm)	Series	CD17
Voltage - Rated500VDielectric MaterialMicaOperating Temperature-55°C ~ 150°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.232" (5.90mm)FeaturesRF, High Q, Low LossSize / Dimension0.469" L x 0.209" W (11.90mm x 5.30mm)Height - Seated (Max)0.390" (9.90mm)	Capacitance	330pF
Dielectric MaterialMicaOperating Temperature-55°C ~ 150°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.232" (5.90mm)FeaturesRF, High Q, Low LossSize / Dimension0.469" L x 0.209" W (11.90mm x 5.30mm)Height - Seated (Max)0.390" (9.90mm)	Tolerance	±5%
Operating Temperature-55°C ~ 150°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.232" (5.90mm)FeaturesRF, High Q, Low LossSize / Dimension0.469" L x 0.209" W (11.90mm x 5.30mm)Height - Seated (Max)0.390" (9.90mm)	Voltage - Rated	500V
Nounting TypeThrough HolePackage / CaseRadialLead Spacing0.232" (5.90mm)FeaturesRF, High Q, Low LossSize / Dimension0.469" L x 0.209" W (11.90mm x 5.30mm)Height - Seated (Max)0.390" (9.90mm)	Dielectric Material	Mica
Package / CaseRadialLead Spacing0.232" (5.90mm)FeaturesRF, High Q, Low LossSize / Dimension0.469" L x 0.209" W (11.90mm x 5.30mm)Height - Seated (Max)0.390" (9.90mm)	Operating Temperature	-55°C ~ 150°C
Lead Spacing 0.232" (5.90mm)   Features RF, High Q, Low Loss   Size / Dimension 0.469" L x 0.209" W (11.90mm x 5.30mm)   Height - Seated (Max) 0.390" (9.90mm)	Mounting Type	Through Hole
Features RF, High Q, Low Loss   Size / Dimension 0.469" L x 0.209" W (11.90mm x 5.30mm)   Height - Seated (Max) 0.390" (9.90mm)	Package / Case	Radial
Size / Dimension 0.469" L x 0.209" W (11.90mm x 5.30mm)   Height - Seated (Max) 0.390" (9.90mm)	Lead Spacing	0.232" (5.90mm)
Height - Seated (Max) 0.390" (9.90mm)	Features	RF, High Q, Low Loss
	Size / Dimension	0.469" L x 0.209" W (11.90mm x 5.30mm)
	Height - Seated (Max)	0.390" (9.90mm)
Report errors?		Report errors?

#### **CD17FD331JO3** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE GUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# **CD17FD331JO3 Payment Methods**



# **CD17FD331JO3** Shipping Methods



If you have any question about CD17FD331JO3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com