



CD4009UBPWE4 Information

west meisoner com

For Reference Only

Part Number CD4009UBPWE4

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)
Logic - Gates and Inverters

Description IC HEX INVERT BUFF/CONV 16-TSSOP

Package 16-TSSOP (0.173", 4.40mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CD4009UBPWE4 Specifications

Manufacturer Part Number CD4009UBPWE4 Manufacturer Texas Instruments Category Integrated Circuits (ICs) Logic - Gates and Inverters Logic - Gates and Inverters Package 16-TSSOP (0.173", 4.40mm Width) Series 4000B Logic Type Inverter Number of Circuits 6 Number of Inputs 6 Features - Voltage - Supply 3 V ~ 18 V Current - Quiescent (Max) 4μA Current - Output High, Low 1.5mA, 24mA Logic Level - Low 1 V ~ 2.5 V Logic Level - High 4 V ~ 12.5 V
$ \begin{array}{c} \text{Category} & \text{Integrated Circuits (ICs)} \\ & \text{Logic - Gates and Inverters} \\ \text{Package} & 16\text{-TSSOP (0.173", 4.40mm Width)} \\ \text{Series} & 4000B \\ \text{Logic Type} & \text{Inverter} \\ \text{Number of Circuits} & 6 \\ \text{Number of Inputs} & 6 \\ \text{Features} & - \\ \text{Voltage - Supply} & 3 \text{ V} \sim 18 \text{ V} \\ \text{Current - Quiescent (Max)} & 4\mu\text{A} \\ \text{Current - Output High, Low} & 1.5\text{mA, 24mA} \\ \text{Logic Level - Low} & 1 \text{ V} \sim 2.5 \text{ V} \\ \text{Logic Level - High} & 4 \text{ V} \sim 12.5 \text{ V} \\ \end{array} $
$\begin{array}{c} Logic - Gates \ and \ Inverters \\ \\ Package & 16\text{-TSSOP} \ (0.173", 4.40mm \ Width) \\ \\ Series & 4000B \\ \\ Logic \ Type & Inverter \\ \\ Number \ of \ Circuits & 6 \\ \\ Number \ of \ Inputs & 6 \\ \\ Features & - \\ \\ Voltage - Supply & 3 \ V \sim 18 \ V \\ \\ Current - Quiescent \ (Max) & 4\mu A \\ \\ Current - Output \ High, \ Low & 1.5mA, 24mA \\ \\ Logic \ Level - Low & 1 \ V \sim 2.5 \ V \\ \\ Logic \ Level - High & 4 \ V \sim 12.5 \ V \\ \end{array}$
Package $ 16\text{-TSSOP } (0.173'', 4.40 \text{mm Width}) $ Series $ 4000B $ Logic Type $ Inverter $ Number of Circuits $ 6 $ Number of Inputs $ 6 $ Features $ - $ Voltage - Supply $ 3 \text{ V} \sim 18 \text{ V} $ Current - Quiescent (Max) $ 4\mu A $ Current - Output High, Low $ 1.5mA, 24mA $ Logic Level - Low $ 1 \text{ V} \sim 2.5 \text{ V} $ Logic Level - High $ 4 \text{ V} \sim 12.5 \text{ V} $
Logic TypeInverterNumber of Circuits6Number of Inputs6Features-Voltage - Supply $3 \text{ V} \sim 18 \text{ V}$ Current - Quiescent (Max) $4\mu\text{A}$ Current - Output High, Low $1.5\text{mA}, 24\text{mA}$ Logic Level - Low $1 \text{ V} \sim 2.5 \text{ V}$ Logic Level - High $4 \text{ V} \sim 12.5 \text{ V}$
$\begin{array}{llllllllllllllllllllllllllllllllllll$
Number of Inputs 6 Features - Voltage - Supply 3 $V \sim 18 V$ Current - Quiescent (Max) 4 μ A Current - Output High, Low 1.5mA, 24mA Logic Level - Low 1 $V \sim 2.5 V$ Logic Level - High 4 $V \sim 12.5 V$
Features - Voltage - Supply 3 V ~ 18 V Current - Quiescent (Max) 4 μ A Current - Output High, Low 1.5mA, 24mA Logic Level - Low 1 V ~ 2.5 V Logic Level - High 4 V ~ 12.5 V
Voltage - Supply $3\ V \sim 18\ V$ Current - Quiescent (Max) $4\mu A$ Current - Output High, Low $1.5mA, 24mA$ Logic Level - Low $1\ V \sim 2.5\ V$ Logic Level - High $4\ V \sim 12.5\ V$
$\begin{array}{lll} & & & & & \\ & & & & \\ & & & \\ & & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ &$
Current - Output High, Low $1.5\text{mA}, 24\text{mA}$ Logic Level - Low $1 \text{ V} \sim 2.5 \text{ V}$ Logic Level - High $4 \text{ V} \sim 12.5 \text{ V}$
Logic Level - Low $1 \text{ V} \sim 2.5 \text{ V}$ Logic Level - High $4 \text{ V} \sim 12.5 \text{ V}$
Logic Level - High $4 \text{ V} \sim 12.5 \text{ V}$
Max Propagation Delay @ V, Max CL 60ns @ 15V, 50pF
Operating Temperature -55°C ~ 125°C
Mounting Type Surface Mount
Supplier Device Package 16-TSSOP
Package / Case 16-TSSOP (0.173", 4.40mm Width)
Report errors?

CD4009UBPWE4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CD4009UBPWE4 Payment Methods



















CD4009UBPWE4 Shipping Methods













If you have any question about CD4009UBPWE4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com