

CDR01BX472AMZMAT

CDR01BX472AMZMAT Information

Part Number CDR01BX472AMZMAT

Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 4700PF 50V 20% BX 0805

Package 0805 (2012 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CDR01BX472AMZMAT Specifications

Manufacturer Part Number CDR01BX472AMZMAT Manufacturer Vishay Vitramon Category Capacitors Package 0805 (2012 Metric) Series Military, MIL-PRF-55681, CDR01 Capacitance 4700pF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Style -		
Category Capacitors Package 0805 (2012 Metric) Series Military, MIL-PRF-55681, CDR01 Capacitance 4700pF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Manufacturer Part Number	CDR01BX472AMZMAT
Package 0805 (2012 Metric) Series Military, MIL-PRF-55681, CDR01 Capacitance 4700pF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Manufacturer	Vishay Vitramon
Package 0805 (2012 Metric) Series Military, MIL-PRF-55681, CDR01 Capacitance 4700pF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Category	Capacitors
Series Military, MIL-PRF-55681, CDR01 Capacitance 4700pF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -		Ceramic Capacitors
Capacitance4700pFTolerance±20%Voltage - Rated50VTemperature CoefficientBXOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.080" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)-Thickness (Max)0.055" (1.40mm)Lead Spacing-	Package	0805 (2012 Metric)
Tolerance ±20% Voltage - Rated 50V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Series	Military, MIL-PRF-55681, CDR01
Voltage - Rated50VTemperature CoefficientBXOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.080" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)-Thickness (Max)0.055" (1.40mm)Lead Spacing-	Capacitance	4700pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) - Thickness (Max) Lead Spacing -	Tolerance	±20%
Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Voltage - Rated	50V
Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Temperature Coefficient	BX
Ratings - General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Features	Military
Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Applications	General Purpose
Package / Case 0805 (2012 Metric) Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Failure Rate	M (1%)
Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing - 0.055" (1.40mm) -	Package / Case	0805 (2012 Metric)
Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Size / Dimension	0.080" L x 0.050" W (2.03mm x 1.27mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.055" (1.40mm)
Lead Style -	Lead Spacing	-
	Lead Style	-
Report errors?		Report errors?

CDR01BX472AMZMAT Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CDR01BX472AMZMAT Payment Methods



















CDR01BX472AMZMAT Shipping Methods













If you have any question about CDR01BX472AMZMAT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com