

CDR31BP360BFZPAT

CDR31BP360BFZPAT Information

Part Number CDR31BP360BFZPAT

Manufacturer Vishay Vitramon

Category Capacitors
Ceramic Capacitors

Description CAP CER 36PF 100V 1% BP 0805

Package 0805 (2012 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CDR31BP360BFZPAT Specifications

Manufacturer Part Number CDR31BP360BFZPAT Manufacturer Vishay Vitramon Category Capacitors Package 0805 (2012 Metric) Series Military, MIL-PRF-55681, CDR31 Capacitance 36pF Tolerance ±1% Voltage - Rated 100V Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate P (0.1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm)		
Category Capacitors Package 0805 (2012 Metric) Series Military, MIL-PRF-55681, CDR31 Capacitance 36pF Tolerance ±1% Voltage - Rated 100V Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate P (0.1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) -	Manufacturer Part Number	CDR31BP360BFZPAT
Package O805 (2012 Metric) Series Military, MIL-PRF-55681, CDR31 Capacitance 36pF Tolerance ±1% Voltage - Rated 100V Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate P (0.1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) -	Manufacturer	Vishay Vitramon
Package0805 (2012 Metric)SeriesMilitary, MIL-PRF-55681, CDR31Capacitance36pFTolerance±1%Voltage - Rated100VTemperature CoefficientBPOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateP (0.1%)Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-	Category	Capacitors
SeriesMilitary, MIL-PRF-55681, CDR31Capacitance36pFTolerance±1%Voltage - Rated100VTemperature CoefficientBPOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateP (0.1%)Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-		Ceramic Capacitors
Capacitance36pFTolerance±1%Voltage - Rated100VTemperature CoefficientBPOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateP (0.1%)Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-	Package	0805 (2012 Metric)
Tolerance ±1% Voltage - Rated 100V Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate P (0.1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max)	Series	Military, MIL-PRF-55681, CDR31
Voltage - Rated100VTemperature CoefficientBPOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateP (0.1%)Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-	Capacitance	36pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate P (0.1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension Height - Seated (Max) -	Tolerance	$\pm 1\%$
Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate P (0.1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) -	Voltage - Rated	100V
Features Military Ratings - Applications General Purpose Failure Rate P (0.1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) -	Temperature Coefficient	BP
Ratings - General Purpose Failure Rate P (0.1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate P (0.1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) -	Features	Military
Failure Rate P (0.1%) Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) -	Applications	General Purpose
Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) -	Failure Rate	P (0.1%)
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)	Package / Case	0805 (2012 Metric)
	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
Thickness (Max) 0.051" (1.30mm)	Height - Seated (Max)	-
	Thickness (Max)	0.051" (1.30mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

CDR31BP360BFZPAT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CDR31BP360BFZPAT Payment Methods



















CDR31BP360BFZPAT Shipping Methods













If you have any question about CDR31BP360BFZPAT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com