

CDR32BP751BJZRAT

CDR32BP751BJZRAT Information



For Reference Only

Part Number CDR32BP751BJZRAT

Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 750PF 100V 5% BP 1206

Package 1206 (3216 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CDR32BP751BJZRAT Specifications

Manufacturer Part Number CDR32BP751BJZRAT Manufacturer Vishay Vitramon Category Capacitors Package 1206 (3216 Metric) Series Military, MIL-PRF-55681, CDR32 Capacitance 750pF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm)		
Category Capacitors Package 1206 (3216 Metric) Series Military, MIL-PRF-55681, CDR32 Capacitance 750pF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) -	Manufacturer Part Number	CDR32BP751BJZRAT
Package 1206 (3216 Metric) Series Military, MIL-PRF-55681, CDR32 Capacitance 750pF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) -	Manufacturer	Vishay Vitramon
Package1206 (3216 Metric)SeriesMilitary, MIL-PRF-55681, CDR32Capacitance750pFTolerance±5%Voltage - Rated100VTemperature CoefficientBPOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateR (0.01%)Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-	Category	Capacitors
Series Military, MIL-PRF-55681, CDR32 Capacitance 750pF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) -		Ceramic Capacitors
Capacitance750pFTolerance±5%Voltage - Rated100VTemperature CoefficientBPOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateR (0.01%)Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-	Package	1206 (3216 Metric)
Tolerance ±5% Voltage - Rated 100V Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) -	Series	Military, MIL-PRF-55681, CDR32
Voltage - Rated Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension Height - Seated (Max) - BP	Capacitance	750pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension Height - Seated (Max) -	Tolerance	±5%
Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) -	Voltage - Rated	100V
Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) -	Temperature Coefficient	BP
Ratings - General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) -	Features	Military
Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) -	Applications	General Purpose
Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) -	Failure Rate	R (0.01%)
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) -	Package / Case	1206 (3216 Metric)
	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Thickness (Max) 0.051" (1.30mm)	Height - Seated (Max)	-
	Thickness (Max)	0.051" (1.30mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

CDR32BP751BJZRAT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CDR32BP751BJZRAT Payment Methods



















CDR32BP751BJZRAT Shipping Methods













If you have any question about CDR32BP751BJZRAT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com