

# CDR32BP911BFZRAT

## **CDR32BP911BFZRAT Information**



For Reference Only

Part Number CDR32BP911BFZRAT

Manufacturer Vishay Vitramon

**Category** Capacitors

**Ceramic Capacitors** 

**Description** CAP CER 910PF 100V 1% BP 1206

**Package** 1206 (3216 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CDR32BP911BFZRAT Specifications**

Manufacturer Part Number         CDR32BP911BFZRAT           Manufacturer         Vishay Vitramon           Category         Capacitors           Package         1206 (3216 Metric)           Series         Military, MIL-PRF-55681, CDR32           Capacitance         910pF           Tolerance         ±1%           Voltage - Rated         100V           Temperature Coefficient         BP           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Surface Mount, MLCC           Package / Case         1206 (3216 Metric)           Size / Dimension         0.126" L x 0.063" W (3.20mm x 1.60mm)           Height - Seated (Max)         -           Thickness (Max)         0.051" (1.30mm)           Lead Spacing         -		
Category         Capacitors           Package         1206 (3216 Metric)           Series         Military, MIL-PRF-55681, CDR32           Capacitance         910pF           Tolerance         ±1%           Voltage - Rated         100V           Temperature Coefficient         BP           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Surface Mount, MLCC           Package / Case         1206 (3216 Metric)           Size / Dimension         0.126" L x 0.063" W (3.20mm x 1.60mm)           Height - Seated (Max)         -           Thickness (Max)         0.051" (1.30mm)           Lead Spacing         -	Manufacturer Part Number	CDR32BP911BFZRAT
Package         1206 (3216 Metric)           Series         Military, MIL-PRF-55681, CDR32           Capacitance         910pF           Tolerance         ±1%           Voltage - Rated         100V           Temperature Coefficient         BP           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Surface Mount, MLCC           Package / Case         1206 (3216 Metric)           Size / Dimension         0.126" L x 0.063" W (3.20mm x 1.60mm)           Height - Seated (Max)         -           Thickness (Max)         0.051" (1.30mm)           Lead Spacing         -	Manufacturer	Vishay Vitramon
Package         1206 (3216 Metric)           Series         Military, MIL-PRF-55681, CDR32           Capacitance         910pF           Tolerance         ±1%           Voltage - Rated         100V           Temperature Coefficient         BP           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Surface Mount, MLCC           Package / Case         1206 (3216 Metric)           Size / Dimension         0.126" L x 0.063" W (3.20mm x 1.60mm)           Height - Seated (Max)         -           Thickness (Max)         0.051" (1.30mm)           Lead Spacing         -	Category	Capacitors
Series         Military, MIL-PRF-55681, CDR32           Capacitance         910pF           Tolerance         ±1%           Voltage - Rated         100V           Temperature Coefficient         BP           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Surface Mount, MLCC           Package / Case         1206 (3216 Metric)           Size / Dimension         0.126" L x 0.063" W (3.20mm x 1.60mm)           Height - Seated (Max)         -           Thickness (Max)         0.051" (1.30mm)           Lead Spacing         -		Ceramic Capacitors
Capacitance         910pF           Tolerance         ±1%           Voltage - Rated         100V           Temperature Coefficient         BP           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Surface Mount, MLCC           Package / Case         1206 (3216 Metric)           Size / Dimension         0.126" L x 0.063" W (3.20mm x 1.60mm)           Height - Seated (Max)         -           Thickness (Max)         0.051" (1.30mm)           Lead Spacing         -	Package	1206 (3216 Metric)
Tolerance ±1%  Voltage - Rated 100V  Temperature Coefficient BP  Operating Temperature -55°C ~ 125°C  Features Military  Ratings - Applications General Purpose Failure Rate R (0.01%)  Mounting Type Surface Mount, MLCC  Package / Case 1206 (3216 Metric)  Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm)  Height - Seated (Max) -  Thickness (Max) 0.051" (1.30mm)  Lead Spacing -	Series	Military, MIL-PRF-55681, CDR32
Voltage - Rated100VTemperature CoefficientBPOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateR (0.01%)Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.051" (1.30mm)Lead Spacing-	Capacitance	910pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Military  Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) Lead Spacing -	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateR (0.01%)Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.051" (1.30mm)Lead Spacing-	Voltage - Rated	100V
Features Military  Ratings - Applications General Purpose Failure Rate R (0.01%)  Mounting Type Surface Mount, MLCC  Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm)  Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm)  Lead Spacing -	Temperature Coefficient	BP
Ratings - General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate R (0.01%)  Mounting Type Surface Mount, MLCC  Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm)  Height - Seated (Max) -  Thickness (Max) 0.051" (1.30mm)  Lead Spacing -	Features	Military
Failure Rate R (0.01%)  Mounting Type Surface Mount, MLCC  Package / Case 1206 (3216 Metric)  Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm)  Height - Seated (Max) -  Thickness (Max) 0.051" (1.30mm)  Lead Spacing -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.051" (1.30mm) Lead Spacing -	Applications	General Purpose
Package / Case       1206 (3216 Metric)         Size / Dimension       0.126" L x 0.063" W (3.20mm x 1.60mm)         Height - Seated (Max)       -         Thickness (Max)       0.051" (1.30mm)         Lead Spacing       -	Failure Rate	R (0.01%)
Size / Dimension         0.126" L x 0.063" W (3.20mm x 1.60mm)           Height - Seated (Max)         -           Thickness (Max)         0.051" (1.30mm)           Lead Spacing         -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  -  0.051" (1.30mm)  -	Package / Case	1206 (3216 Metric)
Thickness (Max) 0.051" (1.30mm)  Lead Spacing -	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.051" (1.30mm)
Lead Style	Lead Spacing	-
Edd Style	Lead Style	-
Report errors?		Report errors?

### **CDR32BP911BFZRAT Guarantees**



### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **CDR32BP911BFZRAT Payment Methods**





















## **CDR32BP911BFZRAT Shipping Methods**













If you have any question about CDR32BP911BFZRAT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com