

CDR33BX823AMZMAT

CDR33BX823AMZMAT Information



For Reference Only

Part Number CDR33BX823AMZMAT

Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.082UF 50V 20% BX 1210

Package 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CDR33BX823AMZMAT Specifications

Manufacturer Part Number CDR33BX823AMZMAT Manufacturer Vishay Vitramon Category Capacitors Package 1210 (3225 Metric) Series Military, MIL-PRF-55681, CDR33 Capacitance 0.082µF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -		
Category Capacitors Package 1210 (3225 Metric) Series Military, MIL-PRF-55681, CDR33 Capacitance 0.082μF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Manufacturer Part Number	CDR33BX823AMZMAT
Package 1210 (3225 Metric) Series Military, MIL-PRF-55681, CDR33 Capacitance 0.082µF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Manufacturer	Vishay Vitramon
Package 1210 (3225 Metric) Series Military, MIL-PRF-55681, CDR33 Capacitance 0.082µF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Category	Capacitors
Series Military, MIL-PRF-55681, CDR33 Capacitance 0.082µF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 0.082μF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Package	1210 (3225 Metric)
Tolerance ±20% Voltage - Rated 50V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Series	Military, MIL-PRF-55681, CDR33
Voltage - Rated50VTemperature CoefficientBXOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.059" (1.50mm)Lead Spacing-Lead Style-	Capacitance	0.082μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style BX Military General Purpose General Purpose General Purpose General Purpose General Purpose M (1%) General Purpose General Purp	Tolerance	±20%
Operating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.059" (1.50mm)Lead Spacing-Lead Style-	Voltage - Rated	50V
FeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.059" (1.50mm)Lead Spacing-Lead Style-	Temperature Coefficient	BX
Ratings - General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Features	Military
Failure Rate M (1%) Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Failure Rate	M (1%)
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	1210 (3225 Metric)
Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.059" (1.50mm)
	Lead Spacing	-
	Lead Style	-
Report errors?		Report errors?

CDR33BX823AMZMAT Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CDR33BX823AMZMAT Payment Methods



















CDR33BX823AMZMAT Shipping Methods













If you have any question about CDR33BX823AMZMAT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com