

## CDR34BP822AJZRAT

### **CDR34BP822AJZRAT Information**



For Reference Only

Part Number CDR34BP822AJZRAT

Manufacturer Vishay Vitramon

**Category** Capacitors

Ceramic Capacitors

**Description** CAP CER 8200PF 50V 5% BP 1812

Package 1812 (4532 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **CDR34BP822AJZRAT Specifications**

Manufacturer Part Number         CDR34BP822AJZRAT           Manufacturer         Vishay Vitramon           Category         Capacitors           Package         1812 (4532 Metric)           Series         Military, MIL-PRF-55681, CDR34           Capacitance         8200pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         BP           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.059" (1.50mm)           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         1812 (4532 Metric)           Series         Military, MIL-PRF-55681, CDR34           Capacitance         8200pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         BP           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.059" (1.50mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	CDR34BP822AJZRAT
Package         1812 (4532 Metric)           Series         Military, MIL-PRF-55681, CDR34           Capacitance         8200pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         BP           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.059" (1.50mm)           Lead Spacing         -           Lead Style         -	Manufacturer	Vishay Vitramon
Package         1812 (4532 Metric)           Series         Military, MIL-PRF-55681, CDR34           Capacitance         8200pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         BP           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.059" (1.50mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         Military, MIL-PRF-55681, CDR34           Capacitance         8200pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         BP           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.059" (1.50mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         8200pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         BP           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.059" (1.50mm)           Lead Spacing         -           Lead Style         -	Package	1812 (4532 Metric)
Tolerance ±5%  Voltage - Rated 50V  Temperature Coefficient BP  Operating Temperature -55°C ~ 125°C  Features Military  Ratings -  Applications General Purpose Failure Rate R (0.01%)  Mounting Type Surface Mount, MLCC  Package / Case 1812 (4532 Metric)  Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm)  Height - Seated (Max) -  Thickness (Max) 0.059" (1.50mm)  Lead Spacing -  Lead Style -	Series	Military, MIL-PRF-55681, CDR34
Voltage - Rated50VTemperature CoefficientBPOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateR (0.01%)Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.059" (1.50mm)Lead Spacing-Lead Style-	Capacitance	8200pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style  BP  Operating Temperature -55°C ~ 125°C  Military  General Purpose General Purpose  1 8 (0.01%)  1 0 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateR (0.01%)Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.059" (1.50mm)Lead Spacing-Lead Style-	Voltage - Rated	50V
Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Temperature Coefficient	BP
Ratings - General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate R (0.01%)  Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm)  Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm)  Lead Spacing - Lead Style -	Features	Military
Failure Rate R (0.01%)  Mounting Type Surface Mount, MLCC  Package / Case 1812 (4532 Metric)  Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm)  Height - Seated (Max) -  Thickness (Max) 0.059" (1.50mm)  Lead Spacing -  Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case       1812 (4532 Metric)         Size / Dimension       0.177" L x 0.126" W (4.50mm x 3.20mm)         Height - Seated (Max)       -         Thickness (Max)       0.059" (1.50mm)         Lead Spacing       -         Lead Style       -	Failure Rate	R (0.01%)
Size / Dimension       0.177" L x 0.126" W (4.50mm x 3.20mm)         Height - Seated (Max)       -         Thickness (Max)       0.059" (1.50mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	1812 (4532 Metric)
Thickness (Max) 0.059" (1.50mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.177" L x 0.126" W (4.50mm x 3.20mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.059" (1.50mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

#### **CDR34BP822AJZRAT Guarantees**



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **CDR34BP822AJZRAT Payment Methods**



















### **CDR34BP822AJZRAT Shipping Methods**













If you have any question about CDR34BP822AJZRAT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com