

CDR35BP133AFZRAT

CDR35BP133AFZRAT Information



For Reference Only

Part Number CDR35BP133AFZRAT

Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.013UF 50V 1% BP 1825

Package 1825 (4564 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CDR35BP133AFZRAT Specifications

Manufacturer Part Number CDR35BP133AFZRAT Manufacturer Vishay Vitramon Category Capacitors Package 1825 (4564 Metric) Series Military, MIL-PRF-55681, CDR35 Capacitance 0.013µF Tolerance ±1% Voltage - Rated 50V Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -		
Category Capacitors Package 1825 (4564 Metric) Series Military, MIL-PRF-55681, CDR35 Capacitance 0.013µF Tolerance ±1% Voltage - Rated 50V Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Manufacturer Part Number	CDR35BP133AFZRAT
Package 1825 (4564 Metric) Series Military, MIL-PRF-55681, CDR35 Capacitance 0.013μF Tolerance ±1% Voltage - Rated 50V Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Manufacturer	Vishay Vitramon
Package 1825 (4564 Metric) Series Military, MIL-PRF-55681, CDR35 Capacitance 0.013μF Tolerance ±1% Voltage - Rated 50V Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Category	Capacitors
Series Military, MIL-PRF-55681, CDR35 Capacitance 0.013µF Tolerance ±1% Voltage - Rated 50V Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 0.013μF Tolerance ±1% Voltage - Rated 50V Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Package	1825 (4564 Metric)
Tolerance ±1% Voltage - Rated 50V Temperature Coefficient BP Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Series	Military, MIL-PRF-55681, CDR35
Voltage - Rated50VTemperature CoefficientBPOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateR (0.01%)Mounting TypeSurface Mount, MLCCPackage / Case1825 (4564 Metric)Size / Dimension0.177" L x 0.252" W (4.50mm x 6.40mm)Height - Seated (Max)-Thickness (Max)0.059" (1.50mm)Lead Spacing-Lead Style-	Capacitance	0.013μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Tolerance	±1%
Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Voltage - Rated	50V
Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Temperature Coefficient	BP
Ratings - General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Features	Military
Failure Rate R (0.01%) Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Failure Rate	R (0.01%)
Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	1825 (4564 Metric)
Thickness (Max) 0.059" (1.50mm) Lead Spacing - Lead Style -	Size / Dimension	0.177" L x 0.252" W (4.50mm x 6.40mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.059" (1.50mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

CDR35BP133AFZRAT Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CDR35BP133AFZRAT Payment Methods



















CDR35BP133AFZRAT Shipping Methods













If you have any question about CDR35BP133AFZRAT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com