

CDS15ED200JO3

a Quote

CDS15ED200JO3 Information

Contract territors and they	Part Number	CDS15ED200JO3	
	Manufacturer	Cornell Dubilier Electronics (CDE)	同型
	Category	Capacitors Mica and PTFE Capacitors	540
	Description	CAP MICA 20PF 5% 500V RADIAL	- 690
	Package	Radial	
		For the pricing/inventory/lead time, please contact	- Ein
For Reference Only		us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Reques

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CDS15ED200JO3 Specifications

ManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsMica and PTFE CapacitorsPackageRadialSeriesCDS15Capacitance20pFTolerance±5%Voltage - Rated500VDielectric MaterialMicaOperating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.234" (5.90mm)FeaturesGeneral PurposeSize / Dimension0.430" L x 0.140" W (10.90mm x 3.60mm)		
CategoryCapacitorsMica and PTFE CapacitorsPackageRadialSeriesCDS15Capacitance20pFTolerance±5%Voltage - Rated500VDielectric MaterialMicaOperating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.234" (5.90mm)FeaturesGeneral PurposeSize / Dimension0.430" L x 0.140" W (10.90mm x 3.60mm)Height - Seated (Max)0.280" (7.10mm)	Manufacturer Part Number	CDS15ED200JO3
Mica and PTFE CapacitorsPackageRadialSeriesCDS15Capacitance20pFTolerance±5%Voltage - Rated500VDielectric MaterialMicaOperating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.234" (5.90mm)FeaturesGeneral PurposeSize / Dimension0.430" L x 0.140" W (10.90mm x 3.60mm)Height - Seated (Max)0.280" (7.10mm)	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadialPackageCDS15Capacitance20pFTolerance±5%Voltage - Rated500VDielectric MaterialMicaOperating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.234" (5.90mm)FeaturesGeneral PurposeSize / Dimension0.430" L x 0.140" W (10.90mm x 3.60mm)Height - Seated (Max)0.280" (7.10mm)	Category	Capacitors
SeriesCDS15Capacitance20pFTolerance±5%Voltage - Rated500VDielectric MaterialMicaOperating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.234" (5.90mm)FeaturesGeneral PurposeSize / Dimension0.430" L x 0.140" W (10.90mm x 3.60mm)Height - Seated (Max)0.280" (7.10mm)		Mica and PTFE Capacitors
Capacitance20pFTolerance±5%Voltage - Rated500VDielectric MaterialMicaOperating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.234" (5.90mm)FeaturesGeneral PurposeSize / Dimension0.430" L x 0.140" W (10.90mm x 3.60mm)Height - Seated (Max)0.280" (7.10mm)	Package	Radial
Tolerance±5%Voltage - Rated500VDielectric MaterialMicaOperating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.234" (5.90mm)FeaturesGeneral PurposeSize / Dimension0.430" L x 0.140" W (10.90mm x 3.60mm)Height - Seated (Max)0.280" (7.10mm)	Series	CDS15
Voltage - Rated500VDielectric MaterialMicaOperating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.234" (5.90mm)FeaturesGeneral PurposeSize / Dimension0.430" L x 0.140" W (10.90mm x 3.60mm)Height - Seated (Max)0.280" (7.10mm)	Capacitance	20pF
Dielectric MaterialMicaOperating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.234" (5.90mm)FeaturesGeneral PurposeSize / Dimension0.430" L x 0.140" W (10.90mm x 3.60mm)Height - Seated (Max)0.280" (7.10mm)	Tolerance	$\pm 5\%$
Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialLead Spacing0.234" (5.90mm)FeaturesGeneral PurposeSize / Dimension0.430" L x 0.140" W (10.90mm x 3.60mm)Height - Seated (Max)0.280" (7.10mm)	Voltage - Rated	500V
Nounting TypeThrough HolePackage / CaseRadialLead Spacing0.234" (5.90mm)FeaturesGeneral PurposeSize / Dimension0.430" L x 0.140" W (10.90mm x 3.60mm)Height - Seated (Max)0.280" (7.10mm)	Dielectric Material	Mica
Package / CaseRadialLead Spacing0.234" (5.90mm)FeaturesGeneral PurposeSize / Dimension0.430" L x 0.140" W (10.90mm x 3.60mm)Height - Seated (Max)0.280" (7.10mm)	Operating Temperature	-55°C ~ 125°C
Lead Spacing 0.234" (5.90mm) Features General Purpose Size / Dimension 0.430" L x 0.140" W (10.90mm x 3.60mm) Height - Seated (Max) 0.280" (7.10mm)	Mounting Type	Through Hole
Features General Purpose Size / Dimension 0.430" L x 0.140" W (10.90mm x 3.60mm) Height - Seated (Max) 0.280" (7.10mm)	Package / Case	Radial
Size / Dimension 0.430" L x 0.140" W (10.90mm x 3.60mm) Height - Seated (Max) 0.280" (7.10mm)	Lead Spacing	0.234" (5.90mm)
Height - Seated (Max) 0.280" (7.10mm)	Features	General Purpose
	Size / Dimension	0.430" L x 0.140" W (10.90mm x 3.60mm)
Report errors?	Height - Seated (Max)	0.280" (7.10mm)
		Report errors?

CDS15ED200JO3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CDS15ED200JO3 Payment Methods





If you have any question about CDS15ED200JO3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com