

CE3292-4.000 Information

Heisener.com

Part Number CE3292-4.000

Manufacturer Crystek Corporation

Category Crystals, Oscillators, Resonators

Oscillators

Description OSC XO 4.000MHZ HCMOS TTL SMD

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CE3292-4.000 Specifications

Manufacturer CE3292-4.000 Manufacturer Crystek Corporation Category Crystals, Oscillators, Resonators Oscillators Oscillators Package 4-SMD, No Lead Series C3292 Type XO (Standard) Frequency 4MHz Function Enable/Disable Output HCMOS, TTL Voltage - Supply 5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) 60mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.283" L x 0.198" W (7.20mm x 5.02mm)		
Category Crystals, Oscillators, Resonators Oscillators Package 4-SMD, No Lead Series C3292 Type XO (Standard) Frequency 4MHz Function Cutput HCMOS, TTL Voltage - Supply Frequency Stability Operating Temperature -40°C ~ 85°C Current - Supply (Max) Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Manufacturer Part Number	CE3292-4.000
Oscillators Package 4-SMD, No Lead Series C3292 Type XO (Standard) Frequency 4MHz Function Enable/Disable Output HCMOS, TTL Voltage - Supply 5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) 60mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Manufacturer	Crystek Corporation
Package 4-SMD, No Lead Series C3292 Type XO (Standard) Frequency 4MHz Function Enable/Disable Output HCMOS, TTL Voltage - Supply 5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) 60mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Category	Crystals, Oscillators, Resonators
Series C3292 Type XO (Standard) Frequency 4MHz Function Enable/Disable Output HCMOS, TTL Voltage - Supply 5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) 60mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead		Oscillators
Type XO (Standard) Frequency 4MHz Function Enable/Disable Output HCMOS, TTL Voltage - Supply 5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) 60mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Package	4-SMD, No Lead
Frequency 4MHz Function Enable/Disable Output HCMOS, TTL Voltage - Supply 5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) 60mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Series	C3292
Function Enable/Disable Output HCMOS, TTL Voltage - Supply 5V Frequency Stability Operating Temperature -40°C ~ 85°C Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case Enable/Disable HCMOS, TTL 5V 60MA -40°C ~ 85°C Current - Supply (Max) 60mA Surface Mount Package / Case 4-SMD, No Lead	Туре	XO (Standard)
Output HCMOS, TTL Voltage - Supply 5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) 60mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Frequency	4MHz
Voltage - Supply Frequency Stability Departing Temperature -40°C ~ 85°C Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 5V ±50ppm -40°C ~ 85°C 60mA Fackage / Case - Surface Mount 4-SMD, No Lead	Function	Enable/Disable
Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) 60mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Output	HCMOS, TTL
Operating Temperature -40°C ~ 85°C Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Voltage - Supply	5V
Current - Supply (Max) 60mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Frequency Stability	±50ppm
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Operating Temperature	-40°C ~ 85°C
Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Current - Supply (Max)	60mA
Package / Case 4-SMD, No Lead	Ratings	-
	Mounting Type	Surface Mount
Size / Dimension 0.283" L x 0.198" W (7.20mm x 5.02mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.283" L x 0.198" W (7.20mm x 5.02mm)
Height - Seated (Max) 0.071" (1.80mm)	Height - Seated (Max)	0.071" (1.80mm)
Report errors?		Report errors?

CE3292-4.000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CE3292-4.000 Payment Methods



















CE3292-4.000 Shipping Methods













If you have any question about CE3292-4.000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com