

# CENB1020A0503F01

#### CENB1020A0503F01 Information

	Part Number	CENB1020A0503F01	
www.heisenter.com	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands	
	Category	Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters	
	Description	AC/DC DESKTOP ADAPTER 5V 20W	20582
	Package	-	国際登場
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## CENB1020A0503F01 Specifications

ManufacturerSL Power Electronics Manufacture of Condor/Ault BrandsCategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesCENB 1020Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)3APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)		
Category   Power Supplies - External/Internal (Off-Board)     AC DC Desktop, Wall Adapters     Package   -     Series   CENB 1020     Region Utilized   International     Form   Desktop (Class I)     Input Type   Cord (Sold Separately)     Voltage - Input   100 ~ 240 VAC     Voltage - Output (Max)   3A     Power (Watts)   15W     No Load Power Consumption   Solivie Center     Applications   ITE (Commercial)     Efficiency   Level V     Operating Temperature   0°C ~ 40°C     Output Connector   Bartel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm     Size / Dimension   3.1" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Manufacturer Part Number	CENB1020A0503F01
AC DC Desktop, Wall AdaptersPackage-SeriesCENB1020Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)3APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands
Package-SeriesCENB1020Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)3APower (Watts)15WNo Load Power Consumption90mW (Max)PolarizationTE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Category	Power Supplies - External/Internal (Off-Board)
Series   CENB1020     Region Utilized   International     Form   Desktop (Class I)     Input Type   Cord (Sold Separately)     Voltage - Input   100 ~ 240 VAC     Voltage - Output   5V     Current - Output (Max)   3A     Power (Watts)   300mW (Max)     Polarization   Positive Center     Applications   ITE (Commercial)     Efficiency   Level V     Operating Temperature   0°C ~ 40°C     Output Connector   Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm     Size / Dimension   3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)3APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Package	-
Form   Desktop (Class I)     Input Type   Cord (Sold Separately)     Voltage - Input   100 ~ 240 VAC     Voltage - Output   5V     Current - Output (Max)   3A     Power (Watts)   15W     No Load Power Consumption   300mW (Max)     Polarization   Positive Center     Applications   ITE (Commercial)     Efficiency   Level V     Operating Temperature   0°C ~ 40°C     Output Connector   Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm     Size / Dimension   3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Series	CENB1020
Input Type   Cord (Sold Separately)     Voltage - Input   100 ~ 240 VAC     Voltage - Output   5V     Current - Output (Max)   3A     Power (Watts)   15W     No Load Power Consumption   300mW (Max)     Polarization   Positive Center     Applications   ITE (Commercial)     Efficiency   Level V     Operating Temperature   0°C ~ 40°C     Output Connector   Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm     Size / Dimension   3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Region Utilized	International
Voltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)3APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Form	Desktop (Class I)
Voltage - Output5VCurrent - Output (Max)3APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Input Type	Cord (Sold Separately)
Current - Output (Max)3APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts)15WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Voltage - Output	5V
No Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Current - Output (Max)	3A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Power (Watts)	15W
ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	No Load Power Consumption	300mW (Max)
EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Polarization	Positive Center
Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Applications	ITE (Commercial)
Output Connector   Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm     Size / Dimension   3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Efficiency	Level V
Size / Dimension 3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Operating Temperature	$0^{\circ}$ C ~ $40^{\circ}$ C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)
		Report errors?

#### CENB1020A0503F01 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# CENB1020A0503F01 Payment Methods



If you have any question about CENB1020A0503F01, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com