

# CENB1030A2451C01

### CENB1030A2451C01 Information

Part Number Manufacturer	CENB1030A2451C01 SL Power Electronics Manufacture of Condor/Ault	
Category	Brands Power Supplies - External/Internal (Off-Board)	
Description	AC DC Desktop, Wall Adapters AC/DC WALL MOUNT ADAPTER 24V 30W	
Package	- For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## CENB1030A2451C01 Specifications

Manufacturer Part Number CENB1030A2451C01   Manufacturer SL Power Electronics Manufacture of Condor/Ault Brands   Category Power Supplies - External/Internal (Off-Board)   Category AC DC Desktop, Wall Adapters   Package -   Series CENB1030   Region Utilized North America   Form Wall Mount   Input Type Fixed Blade, Multi-Blade (Sold Separately)   Voltage - Input 100 ~ 240 VAC   Voltage - Output (Max) 1.33A   Power (Watts) 300mW (Max)   Polarization -   Applications ITE Commercial)   Efficiency Level V   Operating Temperature 0°C ~ 40°C   Output Connector Retangular, 6 Position		
Category Power Supplies - External/Internal (Off-Board)   AC DC Desktop, Wall Adapters   Package -   Series CENB 1030   Region Utilized North America   Form Wall Mount   Input Type Fixed Blade, Multi-Blade (Sold Separately)   Voltage - Input 100 ~ 240 VAC   Voltage - Output (Max) 1.33A   Power (Watts) 300mW (Max)   Polarization -   Applications ITE (Commercial)   Efficiency Level V   Output Connector 0°C ~ 40°C   Output Connector Sectangular, 6 Position   Size / Dimension 3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Manufacturer Part Number	CENB1030A2451C01
AC DC Desktop, Wall AdaptersPackage-SeriesCENB1030Region UtilizedNorth AmericaFormWall MountInput TypeFixed Blade, Multi-Blade (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output24VCurrent - Output (Max)1.33APower (Watts)300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorS.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands
Package-SeriesCENB1030Region UtilizedNorth AmericaFormWall MountInput TypeFixed Blade, Multi-Blade (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output24VCurrent - Output (Max)1.33APower (Watts)300mW (Max)No Load Power Consumption-Polarization-ApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorRectangular, 6 PositionSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 33.6mm)	Category	Power Supplies - External/Internal (Off-Board)
Series CENB1030   Region Utilized North America   Form Wall Mount   Input Type Fixed Blade, Multi-Blade (Sold Separately)   Voltage - Input 100 ~ 240 VAC   Voltage - Output 24V   Current - Output (Max) 1.33A   Power (Watts) 300mW (Max)   No Load Power Consumption 300mW (Max)   Applications ITE (Commercial)   Efficiency Level V   Operating Temperature 0°C ~ 40°C   Output Connector Rectangular, 6 Position   Size / Dimension 3.78" L x 2.17" W x 1.32" H (96.0mm x 35.0mm x 33.6mm)		AC DC Desktop, Wall Adapters
Region Utilized North America   Form Wall Mount   Input Type Fixed Blade, Multi-Blade (Sold Separately)   Voltage - Input 100 ~ 240 VAC   Voltage - Output 24V   Current - Output (Max) 1.33A   Power (Watts) 300mW (Max)   No Load Power Consumption 300mW (Max)   Polarization -   Applications ITE (Commercial)   Efficiency Level V   Operating Temperature 0°C ~ 40°C   Output Connector Rectangular, 6 Position   Size / Dimension 3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Package	-
Form Wall Mount   Input Type Fixed Blade, Multi-Blade (Sold Separately)   Voltage - Input 100 ~ 240 VAC   Voltage - Output 24V   Current - Output (Max) 1.33A   Power (Watts) 32W   No Load Power Consumption 300mW (Max)   Polarization -   Applications TE (Commercial)   Efficiency Level V   Operating Temperature 0°C ~ 40°C   Output Connector Rectangular, 6 Position   Size / Dimension 3.78" L x 2.17" W x 1.32" H (96.0mm x 33.6mm)	Series	CENB1030
Input Type Fixed Blade, Multi-Blade (Sold Separately)   Voltage - Input 100 ~ 240 VAC   Voltage - Output 24V   Current - Output (Max) 1.33A   Power (Watts) 32W   No Load Power Consumption 300mW (Max)   Polarization -   Applications ITE (Commercial)   Efficiency Level V   Operating Temperature 0°C ~ 40°C   Output Connector Rectangular, 6 Position   Size / Dimension 3.78" L x 2.17" W x 1.32" H (96.0mm x 33.6mm)	Region Utilized	North America
Voltage - Input 100 ~ 240 VAC   Voltage - Output 24V   Current - Output (Max) 1.33A   Power (Watts) 32W   No Load Power Consumption 300mW (Max)   Polarization -   Applications ITE (Commercial)   Efficiency Level V   Operating Temperature 0°C ~ 40°C   Output Connector Rectangular, 6 Position   Size / Dimension 3.78" L x 2.17" W x 1.32" H (96.0mm x 33.6mm)	Form	Wall Mount
Voltage - Output24VCurrent - Output (Max)1.33APower (Watts)32WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorRectangular, 6 PositionSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Input Type	Fixed Blade, Multi-Blade (Sold Separately)
Current - Output (Max)1.33APower (Watts)32WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorRectangular, 6 PositionSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 33.6mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts)32WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorRectangular, 6 PositionSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Voltage - Output	24V
No Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorRectangular, 6 PositionSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 33.6mm)	Current - Output (Max)	1.33A
Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorRectangular, 6 PositionSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 33.6mm)	Power (Watts)	32W
ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorRectangular, 6 PositionSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	No Load Power Consumption	300mW (Max)
EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorRectangular, 6 PositionSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Polarization	-
Operating Temperature0°C ~ 40°COutput ConnectorRectangular, 6 PositionSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Applications	ITE (Commercial)
Output ConnectorRectangular, 6 PositionSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Efficiency	Level V
Size / Dimension 3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Operating Temperature	$0^{\circ}$ C ~ $40^{\circ}$ C
	Output Connector	Rectangular, 6 Position
Report errors?	Size / Dimension	3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)
		Report errors?

### CENB1030A2451C01 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### CENB1030A2451C01 Payment Methods



If you have any question about CENB1030A2451C01, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com