

CENB1030A4865C01

CENB1030A4865C01 Information

Heisener.com	Part Number Manufacturer Category Description Package	CENB1030A4865C01 SL Power Electronics Manufacture of Condor/Ault Brands Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC/DC WALL MOUNT ADAPTER 48V 30W	
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CENB1030A4865C01 Specifications

Manufacturer Part NumberCENB 1030A4865C01ManufacturerSL Power Electronics Manufacture of Condor/Ault BrandsCategoryPower Supplies - External/Internal (Off-Board)CategoryAC DC Desktop, Wall AdaptersPackage-SeriesCENB 1030Region UtilizedNorth AmericaFormWall MountInput TypeFixed Blade, Multi-Blade (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output (Max)670mAPower (Watts)32WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOutput ConnectorStriped, Timed Wire LeadsSiz / DimensionSiz% L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series CENB 1030 Region Utilized North America Form Wall Mount Input Type Fixed Blade, Multi-Blade (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output (Max) 670mA Power (Watts) 32W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dimension 3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Manufacturer Part Number	CENB1030A4865C01
AC DC Dektop, Wall AdaptersPackage-SeriesCENB1030Region UtilizedNorth AmericaFormWall MountInput TypeFixed Blade, Multi-Blade (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output48VCurrent - Output (Max)670mAPower (Watts)32WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorStriped, Tinned Wire LeadsSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands
Package-SeriesCENB1030Region UtilizedNorth AmericaFormWall MountInput TypeFixed Blade, Multi-Blade (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output48VCurrent - Output (Max)670mAPower (Watts)32WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 35.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series CENB1030 Region Utilized North America Form Wall Mount Input Type Fixed Blade, Multi-Blade (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 48V Current - Output (Max) 670mA Power (Watts) 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dinension 3.78" L x 2.17" W x 1.32" H (96.0mm x 35.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaRegion UtilizedNorth AmericaFormWall MountInput TypeFixed Blade, Multi-Blade (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output48VCurrent - Output (Max)670mAPower (Watts)32WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 35.0mm x 33.6mm)	Package	-
Form Wall Mount Input Type Fixed Blade, Multi-Blade (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 48V Current - Output (Max) 670mA Power (Watts) 32W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency 0°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Stripped, Tinned Wire Leads 378" L x 2.17" W x 1.32" H (96.0mm x 33.6mm)	Series	CENB1030
Input TypeFixed Blade, Multi-Blade (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output48VCurrent - Output (Max)670mAPower (Watts)32WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Region Utilized	North America
Voltage - Input100 ~ 240 VACVoltage - Output48VCurrent - Output (Max)670mAPower (Watts)32WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 33.6mm)	Form	Wall Mount
Voltage - Output48VCurrent - Output (Max)670mAPower (Watts)32WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Input Type	Fixed Blade, Multi-Blade (Sold Separately)
Current - Output (Max)670mAPower (Watts)32WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 33.6mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts)32WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Voltage - Output	48V
No Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Current - Output (Max)	670mA
Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Power (Watts)	32W
ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	No Load Power Consumption	300mW (Max)
EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Polarization	-
Operating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Applications	ITE (Commercial)
Output ConnectorStripped, Tinned Wire LeadsSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Efficiency	Level V
Size / Dimension 3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Operating Temperature	$0^{\circ}C \sim 40^{\circ}C$
	Output Connector	Stripped, Tinned Wire Leads
Report errors?	Size / Dimension	3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)
		Report errors?

CENB1030A4865C01 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CENB1030A4865C01 Payment Methods



If you have any question about CENB1030A4865C01, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com