

CENB1050A4803N01

CENB1050A4803N01 Information

Heisener.com	Part Number Manufacturer Category	CENB1050A4803N01 SL Power Electronics Manufacture of Condor/Ault Brands Power Supplies - External/Internal (Off-Board)	
	Description Package	AC DC Desktop, Wall Adapters AC/DC DESKTOP ADAPTER 48V 50W	
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CENB1050A4803N01 Specifications

Manufacturer Part NumberCENB 1050A4803N01ManufacturerSL Power Electronics Manufacture of Condor/Ault BrandsCategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesCENB 1050Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output (Max)1.1APower (Watts)300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°C		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesCENB1050Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output48VCurrent - Output (Max)1.1APower (Watts)300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel V	Manufacturer Part Number	CENB1050A4803N01
AC DC Desktop, Wall AdaptersPackage-SeriesCENB1050Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output48VCurrent - Output (Max)1.1APower (Watts)53WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel V	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands
Package-SeriesCENB1050Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output48VCurrent - Output (Max)1.1APower (Watts)53WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel V	Category	Power Supplies - External/Internal (Off-Board)
SeriesCENB1050Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output48VCurrent - Output (Max)1.1APower (Watts)53WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel V		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output48VCurrent - Output (Max)1.1APower (Watts)53WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel V	Package	-
FormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output48VCurrent - Output (Max)1.1APower (Watts)53WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel V	Series	CENB1050
Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output48VCurrent - Output (Max)1.1APower (Watts)53WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel V	Region Utilized	International
Voltage - Input100 ~ 240 VACVoltage - Output48VCurrent - Output (Max)1.1APower (Watts)53WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel V	Form	Desktop (Class II)
Voltage - Output48VCurrent - Output (Max)1.1APower (Watts)53WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel V	Input Type	Cord (Sold Separately)
Current - Output (Max)1.1APower (Watts)53WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel V	Voltage - Input	100 ~ 240 VAC
Power (Watts)53WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel V	Voltage - Output	48V
No Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel V	Current - Output (Max)	1.1A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel V	Power (Watts)	53W
ApplicationsITE (Commercial)EfficiencyLevel V	No Load Power Consumption	300mW (Max)
Efficiency Level V	Polarization	Positive Center
	Applications	ITE (Commercial)
Operating Temperature $0^{\circ}C \sim 40^{\circ}C$	Efficiency	Level V
	Operating Temperature	0° C ~ 40° C
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Size / Dimension 4.25" L x 2.67" W x 1.28" H (108.0mm x 67.7mm x 32.5mm)	Size / Dimension	4.25" L x 2.67" W x 1.28" H (108.0mm x 67.7mm x 32.5mm)
Report err		Report errors?

CENB1050A4803N01 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CENB1050A4803N01 Payment Methods



If you have any question about CENB1050A4803N01, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com