



### **CG101T350R2C Information**

www.helsener.com

For Reference Only

Part Number CG101T350R2C

Manufacturer Cornell Dubilier Electronics (CDE)

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description**CAP ALUM 100UF 350V SCREW**Package**Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **CG101T350R2C Specifications**

Manufacturer Part NumberCG101T350R2CManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsPackageAluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesCGCapacitance100µFTolerance-10%, +50%Voltage - Rated350VESR (Equivalent Series Resistance)720 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1A @ 120HzRipple Current - High Frequency1.23A @ 10kHz
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series CG Capacitance 100µF Tolerance -10%, +50% Voltage - Rated 350V ESR (Equivalent Series Resistance) 1720 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency 1.23A @ 10kHz
Aluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesCGCapacitance100μFTolerance-10%, +50%Voltage - Rated350VESR (Equivalent Series Resistance)720 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1A @ 120HzRipple Current - High Frequency1.23A @ 10kHz
PackageRadial, Can - Screw TerminalsSeriesCGCapacitance100μFTolerance-10%, +50%Voltage - Rated350VESR (Equivalent Series Resistance)720 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1A @ 120HzRipple Current - High Frequency1.23A @ 10kHz
SeriesCGCapacitance $100\mu F$ Tolerance $-10\%, +50\%$ Voltage - Rated $350V$ ESR (Equivalent Series Resistance) $720 \text{ mOhm @ 120Hz}$ Lifetime @ Temp. $2000 \text{ Hrs @ 85°C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $1A @ 120\text{Hz}$ Ripple Current - High Frequency $1.23A @ 10k\text{Hz}$
Capacitance100μFTolerance-10%, +50%Voltage - Rated350VESR (Equivalent Series Resistance)720 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1A @ 120HzRipple Current - High Frequency1.23A @ 10kHz
Tolerance -10%, +50%  Voltage - Rated 350V  ESR (Equivalent Series Resistance) 720 mOhm @ 120Hz  Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1A @ 120Hz  Ripple Current - High Frequency 1.23A @ 10kHz
Voltage - Rated350VESR (Equivalent Series Resistance)720 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1A @ 120HzRipple Current - High Frequency1.23A @ 10kHz
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  1.23A @ 10kHz
Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1A @ 120Hz  Ripple Current - High Frequency 1.23A @ 10kHz
Operating Temperature  -40°C ~ 85°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  1A @ 120Hz  Ripple Current - High Frequency  1.23A @ 10kHz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1A @ 120Hz Ripple Current - High Frequency 1.23A @ 10kHz
Applications General Purpose Ripple Current - Low Frequency 1A @ 120Hz Ripple Current - High Frequency 1.23A @ 10kHz
Ripple Current - Low Frequency  Ripple Current - High Frequency  1A @ 120Hz  1.23A @ 10kHz
Ripple Current - High Frequency 1.23A @ 10kHz
Impedance -
Lead Spacing -
Size / Dimension 1.375" Dia (34.93mm)
Height - Seated (Max) 2.125" (53.98mm)
Surface Mount Land Size -
Mounting Type Chassis Mount
Package / Case Radial, Can - Screw Terminals
Report errors?

#### **CG101T350R2C Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **CG101T350R2C Payment Methods**



















# **CG101T350R2C Shipping Methods**













If you have any question about CG101T350R2C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com