



CG601U075R2C Information

www.heisener.com

For Reference Only

Part Number CG601U075R2C

Manufacturer Cornell Dubilier Electronics (CDE)

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 600UF 75V SCREW **Package** Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CG601U075R2C Specifications

Manufacturer Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series CG Capacitance 600µF Tolerance -10%, +75% Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency Size / Dimension 1.375" Dia (34.93mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Crassis Mount		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series CG Capacitance 600µF Tolerance -10%, +75% Voltage - Rated 75V ESR (Equivalent Series Resistance) 85 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Polar Applications General Purpose Ripple Current - Low Frequency 2.9A @ 120Hz Ripple Current - High Frequency 3.335A @ 10kHz Impedance - Lead Spacing - Size / Dimension 1.375" Dia (34.93mm) Height - Seated (Max) 2.125" (53.98mm) Surface Mount Land Size - Mounting Type Chassis Mount	Manufacturer Part Number	CG601U075R2C
Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series CG Capacitance 600µF Tolerance -10%, +75% Voltage - Rated 75V ESR (Equivalent Series Resistance) 85 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.9A @ 120Hz Ripple Current - High Frequency 3.335A @ 10kHz Impedance - Lead Spacing - Size / Dimension 1.375" Dia (34.93mm) Height - Seated (Max) 2.125" (53.98mm) Surface Mount Land Size - Mounting Type Chassis Mount	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadial, Can - Screw TerminalsSeriesCGCapacitance600μFTolerance-10%, +75%Voltage - Rated75VESR (Equivalent Series Resistance)85 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.9A @ 120HzRipple Current - High Frequency3.335A @ 10kHzImpedance-Lead Spacing-Size / Dimension1.375" Dia (34.93mm)Height - Seated (Max)2.125" (53.98mm)Surface Mount Land Size-Mounting TypeChassis Mount	Category	Capacitors
Series CG Capacitance 600μF Tolerance -10%, +75% Voltage - Rated 75V ESR (Equivalent Series Resistance) 85 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.9A @ 120Hz Ripple Current - High Frequency 3.335A @ 10kHz Impedance - Lead Spacing - Size / Dimension 1.375" Dia (34.93mm) Height - Seated (Max) 2.125" (53.98mm) Surface Mount Land Size - Mounting Type Chassis Mount		Aluminum Electrolytic Capacitors
Capacitance 600µF Tolerance -10%, +75% Voltage - Rated 75V ESR (Equivalent Series Resistance) 85 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.9A @ 120Hz Ripple Current - High Frequency 3.335A @ 10kHz Impedance - Lead Spacing - Size / Dimension 1.375" Dia (34.93mm) Height - Seated (Max) 2.125" (53.98mm) Surface Mount Land Size - Mounting Type Chassis Mount	Package	Radial, Can - Screw Terminals
Tolerance -10%, +75% Voltage - Rated 75V ESR (Equivalent Series Resistance) 85 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.9A @ 120Hz Ripple Current - High Frequency 3.335A @ 10kHz Impedance - Lead Spacing - Size / Dimension 1.375" Dia (34.93mm) Height - Seated (Max) 2.125" (53.98mm) Surface Mount Land Size - Mounting Type Chassis Mount	Series	CG
Voltage - Rated ESR (Equivalent Series Resistance) ESSR (Equivalent Series Resistance) EVA SERIOR (Equivalent Series Constitution (Equivalent Se	Capacitance	600μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 3.335A @ 10kHz Impedance Lead Spacing - Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 85 mOhm @ 120Hz 2000 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C -40°C ~	Tolerance	-10%, +75%
Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 3.335A @ 10kHz Impedance - Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 2000 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C -40°	Voltage - Rated	75V
Operating Temperature -40°C ~ 85°C Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 3.335A @ 10kHz Impedance - Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type -40°C ~ 85°C Polar -40°C ~ 85°C Folar -40°C -40	ESR (Equivalent Series Resistance)	85 mOhm @ 120Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.9A @ 120Hz Ripple Current - High Frequency 3.335A @ 10kHz Impedance - Lead Spacing - Size / Dimension 1.375" Dia (34.93mm) Height - Seated (Max) 2.125" (53.98mm) Surface Mount Land Size - Mounting Type Chassis Mount	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency 3.335A @ 10kHz Impedance - Lead Spacing - Size / Dimension 1.375" Dia (34.93mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 3.335A @ 10kHz Impedance - Lead Spacing - Size / Dimension 1.375" Dia (34.93mm) Height - Seated (Max) Surface Mount Land Size Mounting Type 2.9A @ 120Hz 3.335A @ 10kHz - Chassis Mount	Polarization	Polar
Ripple Current - High Frequency 3.335A @ 10kHz Impedance - Lead Spacing - Size / Dimension 1.375" Dia (34.93mm) Height - Seated (Max) 2.125" (53.98mm) Surface Mount Land Size - Mounting Type Chassis Mount	Applications	General Purpose
Impedance - Lead Spacing - Size / Dimension 1.375" Dia (34.93mm) Height - Seated (Max) 2.125" (53.98mm) Surface Mount Land Size - Mounting Type Chassis Mount	Ripple Current - Low Frequency	2.9A @ 120Hz
Lead Spacing - Size / Dimension 1.375" Dia (34.93mm) Height - Seated (Max) 2.125" (53.98mm) Surface Mount Land Size - Mounting Type Chassis Mount	Ripple Current - High Frequency	3.335A @ 10kHz
Size / Dimension 1.375" Dia (34.93mm) Height - Seated (Max) 2.125" (53.98mm) Surface Mount Land Size - Chassis Mount	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount	Lead Spacing	-
Surface Mount Land Size - Chassis Mount Chassis Mount	Size / Dimension	1.375" Dia (34.93mm)
Mounting Type Chassis Mount	Height - Seated (Max)	2.125" (53.98mm)
	Surface Mount Land Size	-
Package / Case Radial Can - Screw Terminals	Mounting Type	Chassis Mount
Radial, Can - Below Tellimials	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

CG601U075R2C Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CG601U075R2C Payment Methods



















CG601U075R2C Shipping Methods













If you have any question about CG601U075R2C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com