



CG952U035V3C Information

www.heisener.com

For Reference Only

Part Number CG952U035V3C

Manufacturer Cornell Dubilier Electronics (CDE)

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 9500UF 35V SCREW

Package Radial, Can - Screw Terminals
For the pricing/inventory/lead time, please contact

116

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CG952U035V3C Specifications

Manufacturer Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Cereires Cereires Cereires Cereires Cog Capacitance Polorance Colory, +75% Voltage - Rated Series Resistance) Cereires Coperating Temperature Coperation Coperati		
Category Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals CCG Capacitance 9500µF Tolerance -10%, +75% Voltage - Rated 35V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Page Agacta Size / Dimension Lead Spacing Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	CG952U035V3C
Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series CG Capacitance 9500µF Tolerance -10%, +75% Voltage - Rated 25 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency -2085 A @ 10kHz Impedance Lead Spacing - Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	Cornell Dubilier Electronics (CDE)
Package Radial, Can - Screw Terminals Series CG Capacitance 9500µF Tolerance -10%, +75% Voltage - Rated 35V ESR (Equivalent Series Resistance) 25 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7.9A @ 120Hz Ripple Current - High Frequency 9.085A @ 10kHz Impedance - Lead Spacing - Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 3.125" (79.38mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Category	Capacitors
CG Capacitance 9500µF Tolerance -10%, +75% Voltage - Rated 25 mOhm @ 120Hz ESR (Equivalent Series Resistance) 25 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 9.085A @ 10kHz Impedance - Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Rated -10%, +75% -10% -10% -10% -10% -10% -10% -10% -10		Aluminum Electrolytic Capacitors
Capacitance 9500μF Tolerance -10%, +75% Voltage - Rated 35V ESR (Equivalent Series Resistance) 25 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Polar Applications General Purpose Ripple Current - Low Frequency 7.9A @ 120Hz Ripple Current - High Frequency 9.085A @ 10kHz Impedance - Lead Spacing - Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 3.125" (79.38mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance -10%, +75% Voltage - Rated 35V ESR (Equivalent Series Resistance) 25 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7.9A @ 120Hz Ripple Current - High Frequency 9.085A @ 10kHz Impedance - Lead Spacing - Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 3.125" (79.38mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	CG
Voltage - Rated 25 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 9.085A @ 120Hz Impedance - Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Polar 2000 Hrs @ 85°C -40°C ~ 85°C General Purpose 7.9A @ 120Hz 9.085A @ 10kHz 1	Capacitance	9500μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Polar Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Polar 2000 Hrs @ 85°C -40°C ~ 85°C	Tolerance	-10%, +75%
Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 7.9A @ 120Hz Ripple Current - High Frequency 9.085A @ 10kHz Impedance - Lead Spacing Size / Dimension 4.000" Dia (50.80mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Voltage - Rated	35V
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency Ripple Current - High Frequency	ESR (Equivalent Series Resistance)	25 mOhm @ 120Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7.9A @ 120Hz Ripple Current - High Frequency 9.085A @ 10kHz Impedance - Lead Spacing - Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 3.125" (79.38mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose 7.9A @ 120Hz Ripple Current - High Frequency 9.085A @ 10kHz Impedance - Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case General Purpose 7.9A @ 120Hz 9.085A @ 10kHz - 2.000" Dia (50.80mm) 3.125" (79.38mm) Chassis Mount Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 9.085A @ 10kHz Impedance - Lead Spacing - Size / Dimension 4.000" Dia (50.80mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency 9.085A @ 10kHz Impedance - Lead Spacing - Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance - Lead Spacing - Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 3.125" (79.38mm) Surface Mount Land Size - Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - Low Frequency	7.9A @ 120Hz
Lead Spacing - Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 3.125" (79.38mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	9.085A @ 10kHz
Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) Surface Mount Land Size - Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	-
Surface Mount Land Size - Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.000" Dia (50.80mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	3.125" (79.38mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

CG952U035V3C Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CG952U035V3C Payment Methods





















CG952U035V3C Shipping Methods













If you have any question about CG952U035V3C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com