



CGR262U075R3L Information

www.helsener.com

For Reference Only

Part Number CGR262U075R3L

Manufacturer Cornell Dubilier Electronics (CDE)

Category Capacitors

Aluminum Electrolytic Capacitors

DescriptionCAP ALUM 2600UF 75V SCREWPackageRadial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CGR262U075R3L Specifications

Manufacturer Part NumberCGR262U075R3LManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsPackageRadial, Can - Screw TerminalsSeriesCGRCapacitance2600μFTolerance-10%, +50%Voltage - Rated75VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-		
Category Category Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series CGR Capacitance 2600µF Tolerance -10%, +50% Voltage - Rated 75V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Capacitors Radial, Can - Screw Terminals Aduminum Electrolytic Capacitors Aduminum Electrolytic Capacitors Aduminum Electrolytic Capacitors Aduminum Electrolytic Capacitors Radial, Can - Screw Terminals Capacitance -10%, +50% CGR 2600µF -10%, +50% Corrent - 105°C -105°C -105°C	Manufacturer Part Number	CGR262U075R3L
PackageAluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesCGRCapacitance2600μFTolerance-10%, +50%Voltage - Rated75VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadial, Can - Screw TerminalsSeriesCGRCapacitance2600μFTolerance-10%, +50%Voltage - Rated75VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-	Category	Capacitors
SeriesCGRCapacitance2600μFTolerance-10%, +50%Voltage - Rated75VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-		Aluminum Electrolytic Capacitors
Capacitance2600μFTolerance-10%, +50%Voltage - Rated75VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-	Package	Radial, Can - Screw Terminals
Tolerance -10%, +50% Voltage - Rated 75V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Tolome -10%, +50% 75V 75V 75V 75V 75V 75V - 105°C -40°C ~ 105°C	Series	CGR
Voltage - Rated75 VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-	Capacitance	2600μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) - 2000 Hrs @ 105°C 2000 Hrs @ 105°C -40°C ~ 105°C Polar -40°C ~ 105°C Polar -40°C ~ 105°C	Tolerance	-10%, +50%
Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) -	Voltage - Rated	75V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) -40°C ~ 105°C Polar Polar General Purpose - - - - - - - - - - - - -	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) -	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) General Purpose - General Purpose - Hend Pur	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) -	Polarization	Polar
Ripple Current - High Frequency Impedance	Applications	General Purpose
Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-	Ripple Current - Low Frequency	-
Lead Spacing-Size / Dimension-Height - Seated (Max)-	Ripple Current - High Frequency	-
Size / Dimension - Height - Seated (Max) -	Impedance	-
Height - Seated (Max)	Lead Spacing	-
-	Size / Dimension	-
Surface Mount Land Size -	Height - Seated (Max)	-
	Surface Mount Land Size	-
Mounting Type Chassis Mount	Mounting Type	Chassis Mount
Package / Case Radial, Can - Screw Terminals	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

CGR262U075R3L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CGR262U075R3L Payment Methods



















CGR262U075R3L Shipping Methods













If you have any question about CGR262U075R3L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com