



CGS702T250W4L Information



For Reference Only

Part Number CGS702T250W4L

Manufacturer Cornell Dubilier Electronics (CDE)

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 7000UF 250V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CGS702T250W4L Specifications

Manufacturer Part NumberCGS702T250W4LManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsPackageRadial, Can - Screw TerminalsSeriesCGSCapacitance7000μFTolerance-10%, +50%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series CGS Capacitance 7000µF Tolerance -10%, +50% Voltage - Rated 250V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Capacitors Radial, Can - Screw Terminals Capacitors CGS Radial, Can - Screw Terminals Aduminum Electrolytic Capacitors Radial, Can - Screw Terminals Capacitors Polow Ferminals CGS Capacitance -10%, +50% -10%, +50% CGS Capacitance -2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C -40°C ~ 85°	Manufacturer Part Number	CGS702T250W4L
PackageAluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesCGSCapacitance7000μFTolerance-10%, +50%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadial, Can - Screw TerminalsSeriesCGSCapacitance7000μFTolerance-10%, +50%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-	Category	Capacitors
SeriesCGSCapacitance7000μFTolerance-10%, +50%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-		Aluminum Electrolytic Capacitors
Capacitance 7000μF Tolerance -10%, +50% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) -	Package	Radial, Can - Screw Terminals
Tolerance -10%, +50% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Tolome -10%, +50% 250V	Series	CGS
Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) -	Capacitance	7000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max)	Tolerance	-10%, +50%
Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) -	Voltage - Rated	250V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance Lead Spacing - Size / Dimension - Height - Seated (Max)	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance Lead Spacing Size / Dimension Height - Seated (Max)	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) General Purpose - General Purpose - Hend Pur	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) -	Polarization	Polar
Ripple Current - High Frequency Impedance	Applications	General Purpose
Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-	Ripple Current - Low Frequency	-
Lead Spacing-Size / Dimension-Height - Seated (Max)-	Ripple Current - High Frequency	-
Size / Dimension - Height - Seated (Max) -	Impedance	-
Height - Seated (Max)	Lead Spacing	-
-	Size / Dimension	-
Surface Mount Land Size -	Height - Seated (Max)	-
	Surface Mount Land Size	-
Mounting Type Chassis Mount	Mounting Type	Chassis Mount
Package / Case Radial, Can - Screw Terminals	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

CGS702T250W4L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CGS702T250W4L Payment Methods



















CGS702T250W4L Shipping Methods













If you have any question about CGS702T250W4L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com