



# **CIR00CF-28-15P Information**

Heisener.com

**Part Number** CIR00CF-28-15P **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

CONTRACTOR DIT ACT

**Description** CONN RCPT 35POS PNL MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CIR00CF-28-15P Specifications**

Series MIL-DTL-5015, CIR Connector Type Receptacle, Male Pins Number of Positions 35 Shell Size - Insert 28-15 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver			
Category Circular Connectors Circular Connectors  Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Male Pins Number of Positions 35 Shell Size - Insert 28-15 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated Current Rating 13A	Manufacturer Part Number	CIR00CF-28-15P	
Circular Connectors  Package - Series MIL-DTL-5015, CIR  Connector Type Receptacle, Male Pins  Number of Positions 35  Shell Size - Insert 28-15  Shell Size, MIL - Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Proof  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 113A	Manufacturer	ITT Cannon, LLC	
Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Male Pins Number of Positions 35 Shell Size - Insert 28-15 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Category	Connectors, Interconnects	
Series MIL-DTL-5015, CIR  Connector Type Receptacle, Male Pins  Number of Positions 35  Shell Size - Insert 28-15  Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Proof  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 13A		Circular Connectors	
Connector Type Receptacle, Male Pins Number of Positions 35 Shell Size - Insert 28-15 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Package	-	
Number of Positions  Shell Size - Insert  28-15  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Solder Cup  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Cable Clamp  Voltage - Rated  500VAC, 700VDC  Current Rating  35  Aluminum Alloy, Olive Drab Cadmium Claude  Solver  Solver  Cable Clamp	Series	MIL-DTL-5015, CIR	
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Connector Type	Receptacle, Male Pins	
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Number of Positions	35	
Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 13A	Shell Size - Insert	28-15	
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Shell Size, MIL	-	
Fastening Type  Bayonet Lock Orientation  N (Normal)  Ingress Protection  Environment Proof  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Cable Clamp  Voltage - Rated  500VAC, 700VDC  Current Rating	Mounting Type	Panel Mount, Flange	
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Termination	Solder Cup	
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Fastening Type	Bayonet Lock	
Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Orientation	N (Normal)	
Contact Finish Silver  Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Ingress Protection	Environment Proof	
Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 13A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated	
Voltage - Rated 500VAC, 700VDC Current Rating 13A	Contact Finish	Silver	
Current Rating 13A	Features	Cable Clamp	
	Voltage - Rated	500VAC, 700VDC	
Report errors?	Current Rating	13A	
			Report errors?

### **CIR00CF-28-15P Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **CIR00CF-28-15P Payment Methods**



















### **CIR00CF-28-15P Shipping Methods**













If you have any question about CIR00CF-28-15P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com