



## **CIR01AF-16-10S Information**

Heisener.com

**Part Number** CIR01AF-16-10S **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

**Description** CONN RCPT 3POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **CIR01AF-16-10S Specifications**

Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets  Number of Positions 3  Shell Size - Insert 16-10  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection -  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver			
Category Circular Connectors Circular Connectors  Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 16-10 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated Current Rating 23A	Manufacturer Part Number	CIR01AF-16-10S	
Circular Connectors  Package - Series MIL-DTL-5015, CIR  Connector Type Receptacle, Female Sockets  Number of Positions 3  Shell Size - Insert 16-10  Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 2	Manufacturer	ITT Cannon, LLC	
Package - MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 16-10 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 2	Category	Connectors, Interconnects	
Series MIL-DTL-5015, CIR  Connector Type Receptacle, Female Sockets  Number of Positions 3  Shell Size - Insert 16-10  Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection -  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 23A		Circular Connectors	
Connector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating23A	Package	-	
Number of Positions  Shell Size - Insert  16-10  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Cable Clamp  Voltage - Rated  500VAC, 700VDC  Current Rating  3  Aleminum Alloy, Olive Drab Cadmium Plated  500VAC, 700VDC  Current Rating	Series	MIL-DTL-5015, CIR	
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Cable Clamp  Voltage - Rated  500VAC, 700VDC  Current Rating  23A	Connector Type	Receptacle, Female Sockets	
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Bayonet Lock Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 23A	Number of Positions	3	
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 23A	Shell Size - Insert	16-10	
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 23A	Shell Size, MIL	-	
Fastening Type  Bayonet Lock Orientation  N (Normal)  Ingress Protection  - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 23A	Mounting Type	Free Hanging (In-Line)	
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 23A	Termination	Solder Cup	
Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 23A	Fastening Type	Bayonet Lock	
Shell Material, Finish  Contact Finish  Silver  Features  Cable Clamp  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Cable Clamp  23A	Orientation	N (Normal)	
Contact Finish Silver Cable Clamp Voltage - Rated Current Rating Silver Cable Clamp 23A	Ingress Protection	-	
Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 23A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated	
Voltage - Rated 500VAC, 700VDC Current Rating 23A	Contact Finish	Silver	
Current Rating 23A	Features	Cable Clamp	
	Voltage - Rated	500VAC, 700VDC	
Report errors?	Current Rating	23A	
			Report errors?

#### **CIR01AF-16-10S Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **CIR01AF-16-10S Payment Methods**



















### **CIR01AF-16-10S Shipping Methods**













If you have any question about CIR01AF-16-10S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com