



CIR020R-24-28S-T89 Information

Heisener.com

Part Number CIR020R-24-28S-T89 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 24POS PNL MNT SKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CIR020R-24-28S-T89 Specifications

Manufacturer Part NumberCIR020R-24-28S-T89ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Anodized Black PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Anodized Black PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A	Manufacturer Part Number	CIR020R-24-28S-T89
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Anodized Black PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Anodized Black PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 24 Shell Size - Insert 24-28 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Anodized Black Plated Contact Finish Silver Features Voltage - Rated 200VAC, 250VDC Current Rating 113A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Anodized Black PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A	Package	-
Number of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Anodized Black PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A	Series	MIL-DTL-5015, CIR
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Anodized Black Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 13A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Anodized Black Plated Contact Finish Features - Voltage - Rated 200VAC, 250VDC Current Rating 13A	Number of Positions	24
Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Anodized Black Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 13A	Shell Size - Insert	24-28
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Anodized Black Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 13A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Anodized Black Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 13A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Anodized Black Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 13A	Termination	Solder Cup
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Anodized Black Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum Alloy, Anodized Black Plated Silver - 1 200VAC, 250VDC 13A	Orientation	N (Normal)
Contact Finish Features Voltage - Rated Current Rating Silver - 200VAC, 250VDC 13A	Ingress Protection	Environment Proof
Features - Voltage - Rated 200VAC, 250VDC Current Rating 13A	Shell Material, Finish	Aluminum Alloy, Anodized Black Plated
Voltage - Rated 200VAC, 250VDC Current Rating 13A	Contact Finish	Silver
Current Rating 13A	Features	-
	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	13A
		Report errors?

CIR020R-24-28S-T89 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CIR020R-24-28S-T89 Payment Methods



















CIR020R-24-28S-T89 Shipping Methods













If you have any question about CIR020R-24-28S-T89, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com