



CIR020R-32A-8PX Information

Heisener.com

Part Number CIR020R-32A-8PX
Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 8POS PNL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CIR020R-32A-8PX Specifications

Manufacturer Part Number CIR020R-32A-8PX Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert 32-A8 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation X Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 46A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert32-A8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating46A	Manufacturer Part Number	CIR020R-32A-8PX
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert32-A8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating46A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CIR Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert 32-A8 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation X Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 46A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert32-A8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating46A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert32-A8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating46A	Package	-
Number of Positions8Shell Size - Insert32-A8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating46A	Series	MIL-DTL-5015, CIR
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation X Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating 32-A8 32-A8 32-A8 32-A8 32-A8 32-A8 32-A8 32-A8 48 48 48 48 48 48 48 48 48 48 48 48 48	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation X Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating 46A	Number of Positions	8
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationXIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating46A	Shell Size - Insert	32-A8
Termination Solder Cup Fastening Type Bayonet Lock Orientation X Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 46A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation X Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating	Mounting Type	Panel Mount, Flange
Orientation X Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 46A	Termination	Solder Cup
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 46A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver - 46A	Orientation	X
Contact Finish Silver Features - Voltage - Rated Current Rating 46A	Ingress Protection	Environment Proof
Features - Voltage - Rated 500VAC, 700VDC Current Rating 46A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 46A	Contact Finish	Silver
Current Rating 46A	Features	-
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	46A
		Report errors?

CIR020R-32A-8PX Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CIR020R-32A-8PX Payment Methods





















CIR020R-32A-8PX Shipping Methods













If you have any question about CIR020R-32A-8PX, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com