

Heisener.com

CIR020R-40A-60S-F80-T12-20

CIR020R-40A-60S-F80-T12-20 Information

Part Number CIR020R-40A-60S-F80-T12-20

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 60POS PNL MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CIR020R-40A-60S-F80-T12-20 Specifications

| Manufacturer Part Number CIR020R-40A-60S-F80-T12-20 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 60 Shell Size - Insert 40-A60 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A | | |
|--|--------------------------|---|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions60Shell Size - Insert40-A60Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A | Manufacturer Part Number | CIR020R-40A-60S-F80-T12-20 |
| Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions60Shell Size - Insert40-A60Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A | Manufacturer | ITT Cannon, LLC |
| Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions60Shell Size - Insert40-A60Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A | Category | Connectors, Interconnects |
| SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions60Shell Size - Insert40-A60Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A | | Circular Connectors |
| Connector TypeReceptacle, Female SocketsNumber of Positions60Shell Size - Insert40-A60Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A | Package | - |
| Number of Positions60Shell Size - Insert40-A60Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A | Series | MIL-DTL-5015, CIR |
| Shell Size - Insert 40-A60 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A | Connector Type | Receptacle, Female Sockets |
| Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A | Number of Positions | 60 |
| Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A | Shell Size - Insert | 40-A60 |
| Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A | Shell Size, MIL | - |
| Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating | Mounting Type | Panel Mount, Flange |
| Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A | Termination | Crimp |
| Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A | Fastening Type | Bayonet Lock |
| Shell Material, Finish Contact Finish Gold Features Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Gold 500VAC, 700VDC 13A | Orientation | N (Normal) |
| Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A | Ingress Protection | Environment Proof |
| Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A | Shell Material, Finish | Aluminum Alloy, Olive Drab Cadmium Plated |
| Voltage - Rated 500VAC, 700VDC Current Rating 13A | Contact Finish | Gold |
| Current Rating 13A | Features | - |
| | Voltage - Rated | 500VAC, 700VDC |
| Report errors? | Current Rating | 13A |
| | | Report errors? |

CIR020R-40A-60S-F80-T12-20 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CIR020R-40A-60S-F80-T12-20 Payment Methods



















CIR020R-40A-60S-F80-T12-20 Shipping Methods













If you have any question about CIR020R-40A-60S-F80-T12-20, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com