

Heisener.com

# CIR020R18-10SF80T108

### CIR020R18-10SF80T108 Information

Part Number CIR020R18-10SF80T108

Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 4POS PNL MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CIR020R18-10SF80T108 Specifications

Manufacturer Part Number       CIR020R18-10SF80T108         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-5015, CIR         Connector Type       Receptacle, Female Sockets         Number of Positions       4         Shell Size - Insert       18-10         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Proof         Shell Material, Finish       Aluminum Alloy, Black Zinc Cobalt Plated         Contact Finish       Silver         Features       -         Voltage - Rated       500VAC, 700VDC         Current Rating       23A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert18-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating23A	Manufacturer Part Number	CIR020R18-10SF80T108
Circular ConnectorsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert18-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating23A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 18-10 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 23A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert18-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating23A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert18-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating23A	Package	-
Number of Positions4Shell Size - Insert18-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating23A	Series	MIL-DTL-5015, CIR
Shell Size - Insert 18-10  Shell Size, MIL -  Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Proof  Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Silver  Features -  Voltage - Rated 500VAC, 700VDC  Current Rating 23A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Features Voltage - Rated 500VAC, 700VDC  Current Rating 23A	Number of Positions	4
Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Silver  Features -  Voltage - Rated 500VAC, 700VDC  Current Rating 23A	Shell Size - Insert	18-10
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 23A	Shell Size, MIL	-
Fastening Type  Bayonet Lock Orientation  N (Normal)  Ingress Protection  Environment Proof  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Silver  Features  -  Voltage - Rated  500VAC, 700VDC  Current Rating  23A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 23A	Termination	Crimp
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 23A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Black Zinc Cobalt Plated  Silver  - 200VAC, 700VDC  23A	Orientation	N (Normal)
Contact Finish Silver  Features - Voltage - Rated Current Rating Silver - 23A	Ingress Protection	Environment Proof
Features - Voltage - Rated 500VAC, 700VDC Current Rating 23A	Shell Material, Finish	Aluminum Alloy, Black Zinc Cobalt Plated
Voltage - Rated 500VAC, 700VDC Current Rating 23A	Contact Finish	Silver
Current Rating 23A	Features	-
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	23A
		Report errors?

#### CIR020R18-10SF80T108 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CIR020R18-10SF80T108 Payment Methods



















## CIR020R18-10SF80T108 Shipping Methods













If you have any question about CIR020R18-10SF80T108, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com