

Heisener.com

CIR020R18-8PF80T12

CIR020R18-8PF80T12 Information

Part Number CIR020R18-8PF80T12 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT MALE 8POS GOLD CRIMP

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CIR020R18-8PF80T12 Specifications

Manufacturer Part Number CIR020R18-8PF80T12 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert 18-8 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A			
Canectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert 18-8 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Current Rating 13A, 23A	Manufacturer Part Number	CIR020R18-8PF80T12	
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert18-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A, 23A	Manufacturer	ITT Cannon, LLC	
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert18-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A, 23A	Category	Connectors, Interconnects	
Series MIL-DTL-5015, CIR Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert 18-8 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A		Circular Connectors	
Connector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert18-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A, 23A	Package	-	
Number of Positions Shell Size - Insert 18-8 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A	Series	MIL-DTL-5015, CIR	
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A	Connector Type	Receptacle, Male Pins	
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A	Number of Positions	8	
Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A	Shell Size - Insert	18-8	
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A	Shell Size, MIL	-	
Fastening Type Orientation N (Normal) Ingress Protection Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Bayonet Lock N (Normal) Environment Proof Aluminum Alloy, Olive Drab Cadmium Plated Gold - Voltage - Rated 500VAC, 700VDC Current Rating	Mounting Type	Panel Mount, Flange	
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A	Termination	Crimp	
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A	Fastening Type	Bayonet Lock	
Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A	Orientation	N (Normal)	
Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A	Ingress Protection	Environment Proof	
Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated	
Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A	Contact Finish	Gold	
Current Rating 13A, 23A	Features	-	
•	Voltage - Rated	500VAC, 700VDC	
Report errors?	Current Rating	13A, 23A	
			Report errors?

CIR020R18-8PF80T12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CIR020R18-8PF80T12 Payment Methods



















CIR020R18-8PF80T12 Shipping Methods













If you have any question about CIR020R18-8PF80T12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com