



Heisener.com

CIR020RB-24-21S-F80 Information

Part Number CIR020RB-24-21S-F80
Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT FMALE 10POS SLVR CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CIR020RB-24-21S-F80 Specifications

Manufacturer Part Number CIR020RB-24-21S-F80 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 24-21 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 46A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert24-21Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A, 46A	Manufacturer Part Number	CIR020RB-24-21S-F80
Circular Connectors Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 24-21 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 46A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CIR Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 24-21 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 46A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert24-21Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A, 46A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert24-21Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A, 46A	Package	-
Number of Positions Shell Size - Insert 24-21 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 46A	Series	MIL-DTL-5015, CIR
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 46A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 46A	Number of Positions	10
Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 46A	Shell Size - Insert	24-21
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 46A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 46A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 46A	Termination	Crimp
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 46A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver - 13A, 46A	Orientation	N (Normal)
Contact Finish Features Voltage - Rated Current Rating Silver - Voltage - Rated 900VAC, 1250VDC 13A, 46A	Ingress Protection	Environment Proof
Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 46A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 46A	Contact Finish	Silver
Current Rating 13A, 46A	Features	-
-	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	13A, 46A
		Report errors?

CIR020RB-24-21S-F80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CIR020RB-24-21S-F80 Payment Methods



















CIR020RB-24-21S-F80 Shipping Methods













If you have any question about CIR020RB-24-21S-F80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com